

NEMA

Model JEP0032DP
MFG PN: T56 3U2B

Model JEP0032DP

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
JEP0032DP	3	3490	230/460	3	60	56HJ	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA


Model JEP0032DP
MFG PN: T56 3U2B

ELECTRICAL DATA		
Rated Motor Output Power	3	HP
	-	kW
Rated Motor Speed	3490	r/min 60Hz
	2860	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	7.86-7.26/3.63	A (I _n) @ 60Hz
	8.66/4.33	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	3.38	A (I _n) @ 60Hz
FI Current @ 208V	7.86	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	H	50Hz
Nominal Efficiency	86.5	% @ 60Hz
Nominal Power Factor	0.88	cosΦ @ 60Hz
Leads (Qty, Size)	9	18
Connection	YY/Y	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	47	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	56HJ	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	38 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	304 SS	
NEMA Design	B	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6205 2RS	
Bearing ODE Side	6205 2RS	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T2D	-

Questions? Call 1.888.286.1820

Model JEP0032DP
MFG PN: T56 3U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	3	3
RPM	3490	2860
Voltage	230/460	190/380
Full Load Amps	7.86-7.26/3.63	8.66/4.33
Service Factor	1.25	1
KVA Code	K	H
Full Load Amps (208V)	7.86	-
Nominal Efficiency	86.5	84.4
Nominal Power Factor	0.88	-
Design	B	
Frame	56HJ	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6205 2RS	
Opposite Drive End Bearing	6205 2RS	
Weight (lbs)	38	

NAMEPLATE LAYOUT

TECHTOP		THREE PHASE JET PUMP MOTOR INVERTER DUTY 30:1 VT - 1.0 SF	
MODEL		MFG PN	
	60Hz 50Hz	MFG DATE	
HP		SER #	
RPM		DESIGN	
VOLT		FRAME	
FLA		ENCL. / IP	
SF		DUTY	
KVA CODE		INS CL	
NOM.EFF		AMB	
EFF 75%		DE	
PF		ODE	
USABLE		WEIGHT	lbs
AT 208V			

NEMA
Premium[®]

TECHTOPCANADA.COM

CLASS 1, DIV 2, GROUPS A, B, C AND D COMPLIANT

MADE IN CHINA

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Division II
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model JEP0032DP
MFG PN: T56 3U2B

Torque Speed (T-n) Curve





PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	4.5	271	Start Configuration	DOL
Pull-Up Torque	7.3	162	Starting Current (A)	3.38
Breakdown Torque	14.9	331	No-Load Current (A)	1.6
Full Load Torque	12.2	100	No-Load Power Factor	-


TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	1.8	2.2	2.9	3.6	4.5	4.5
Efficiency (%)	79.2	85.8	87.1	86.6	85.3	85.3
Speed (r/min)	3574	3550	3523	3492	3458	3458
Power Factor (cosΦ)	0.5	0.72	0.83	0.88	0.9	0.9
Input Power (kW)	0.69	1.28	1.89	2.54	3.22	3.22

Questions? Call 1.888.286.1820



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y	ISSUED DATE	04/08/25
CONNECTION:	YY/Y	PREMIUM 56J JET PUMP MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



NEMA Premium TEFC 56HJ

DRAWING NUMBER:	GR3-AL-TF-56HJ	ISSUED DATE	04/08/25
DIMENSIONS:	Inches	PREMIUM 56J JET PUMP MOTORS	
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Cast Aluminum		