

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355724
Catalog # : HT030408NPW22

Frame	: 364/5T	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 30 HP (22 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 230/460 V	Ambient temperature	: -20°C to +40°C
Poles	: 8	Altitude	: 1000 m.a.s.l.
Rated current	: 76.2/38.1 A	Protection degree	: IP55
	: 6.2x(Code G)	Cooling method	: IC411 - TEFC
Rated speed	: 882 rpm	Mounting	: F-1
Rated torque	: 179 ft.lb	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 60.0 dB(A)
Service factor	: 1.25	Starting method	: Direct On Line
Moment of inertia (J)	: 23.5 sq.ft.lb	Approx. weight ³	: 803 lb
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	91.5	91.7	91.7	Max. traction	: 1107 lb
Power Factor	0.62	0.73	0.79	Max. compression	: 1848 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.9	7.7	7.2	3.9	2.8	1.7	1.3

	Drive end	Non drive end
Bearing type	: 6314 C3	6314 C3
Sealing	: WSeal	WSeal
Lubrication interval	: 20000 h	20000 h
Lubricant amount	: 27 g	27 g
Lubricant type	Mobil Polyrex EM	

Notes

USABLE @208V 81.8A SF 1.10 SFA 90.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/06/2026			

Page 1 / 5
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355724

Catalog # : HT030408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 76.2/38.1 A
LRC : 6.2
Rated torque : 179 ft.lb
Locked rotor torque : 160 %
Breakdown torque : 229 %
Rated speed : 882 rpm

Moment of inertia (J) : 23.5 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Duty cycle : Cont.(S1)

Locked rotor time : 45s (cold) 25s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 5 Revision		
Checked by				
Date	29/06/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355724

Catalog # : HT030408NPW22



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	29/06/2026				
				Page 3 / 5	Revision

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355724

Catalog # : HT030408NPW22



Heating constant

Cooling constant

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 4 / 5Revision			
Checked by					
Date	29/06/2026				

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :


Product line : W22 NEMA Premium Efficiency
Three-Phase


Product code : 11355724

Catalog # : HT030408NPW22




Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 5 / 5	Revision
Checked by					
Date	29/06/2026				



D E															A
							Scale						1 : 11		
									HYBRISUSER					00	
	ECM	LOC	SUMMARY OF MODIFICATIONS						EXECUTED	CHECKED	RELEASED	DATE	VER		
	EXECUTED	HYBRISUSER	 THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 364/5T IP55 TEFC						PREVIEW						
	CHECKED														
	RELEASED														
	REL. DATE														
									WDD		00		SHEET		1 / 1

Without vertical jackscrews	
Color RAL 5009	
Painting plan 203A	
Mounting B3R(D)	

DE Shaft End  DUNC 3/4"-10 WEG WPR-7339		
--	--	--