

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11723922
Catalog # : HT040404NPW22

Frame	: 324/6T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 230/460 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 94.2/47.1 A	Protection degree	: IP55
	: 6.1x(Code G)	Cooling method	: IC411 - TEFC
Rated speed	: 1775 rpm	Mounting	: F-1
Rated torque	: 118 ft.lb	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 66.0 dB(A)
Service factor	: 1.25	Starting method	: Direct On Line
Moment of inertia (J)	: 9.16 sq.ft.lb	Approx. weight ³	: 492 lb
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	93.6	94.1	94.1	Max. traction	: 993 lb
Power Factor	0.00	0.72	0.80	0.85	Max. compression	: 1530 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.2	5.4	4.9	2.8	2.0	1.3	0.9

	Drive end	Non drive end
Bearing type	: 6312 C3	6212 C3
Sealing	: V'Ring	V'Ring
Lubrication interval	: 20000 h	20000 h
Lubricant amount	: 21 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes

USABLE @208V 104A SF 1.15 SFA 120A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/06/2026			

Page 1 / 5
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11723922

Catalog # : HT040404NPW22



Performance : 230/460 V 60 Hz 4P

Rated current : 94.2/47.1 A
LRC : 6.1
Rated torque : 118 ft.lb
Locked rotor torque : 229 %
Breakdown torque : 240 %
Rated speed : 1775 rpm

Moment of inertia (J) : 9.16 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Duty cycle : Cont.(S1)

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 5Revision		
Checked by				
Date	29/06/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11723922

Catalog # : HT040404NPW22



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	29/06/2026			Page 3 / 5	Revision

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11723922

Catalog # : HT040404NPW22



Heating constant				
Cooling constant				
Rev.	Changes Summary		Performed	Checked
Performed by				Date
Checked by				
Date	29/06/2026			
			Page 4 / 5	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11723922

Catalog # : HT040404NPW22



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	29/06/2026			Page 5 / 5	Revision

