

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11165995

Frame	: 364/5TS	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 382 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.4485 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	134/67.0	67.4	64.0	61.7	83.1	77.6	74.8
L. R. Amperes [A]	884/442	431	461	457	432	450	471
LRC [A]	6.6x(Code G)	6.4x(Code G)	7.2x(Code H)	7.4x(Code H)	5.2x(Code E)	5.8x(Code F)	6.3x(Code G)
No load current [A]	32.0/16.0	15.8	16.8	17.8	15.8	16.8	17.8
Rated speed [RPM]	3555	2955	2960	2965	2935	2945	2950
Slip [%]	1.25	1.50	1.33	1.17	2.17	1.83	1.67
Rated torque [kgfm]	12.2	12.3	12.3	12.2	14.8	14.8	14.8
Locked rotor torque [%]	200	190	220	229	160	180	190
Breakdown torque [%]	260	250	280	300	200	229	250
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	25s (cold) 14s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)
Noise level ²	79.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)
Efficiency (%)	25%						
	50%	91.7	92.1	91.7	91.6	92.4	92.4
	75%	93.0	92.8	92.8	92.9	93.0	93.0
	100%	93.6	93.7	93.7	93.7	92.4	93.0
Power Factor	25%						
	50%	0.81	0.81	0.79	0.76	0.85	0.83
	75%	0.88	0.88	0.87	0.85	0.88	0.89
	100%	0.90	0.89	0.89	0.89	0.89	0.90

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.3	6.3	6.3	6.3	6.3	6.3
	P2 (0,5;1,0)	4.7	4.7	4.7	4.7	4.7	4.7
	P3 (0,25;1,0)	4.4	4.4	4.4	4.4	4.4	4.4
	P4 (0,9;0,5)	3.3	3.3	3.3	3.3	3.3	3.3
	P5 (0,5;0,5)	1.7	1.7	1.7	1.7	1.7	1.7
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6	0.6	0.6

Bearing type	: 6314 C3	Non drive end	6314 C3	Foundation loads	
Sealing	: WSeal	WSeal		Max. traction	: 223 kgf
Lubrication interval	: 4000 h	4000 h		Max. compression	: 605 kgf
Lubricant amount	: 27 g	27 g			
Lubricant type	: Mobil Polyrex EM				

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	21/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 148A SF 1.10 SFA 163A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995



Performance : 230/460 V 60 Hz 2P

Rated current : 134/67.0 A
LRC : 6.6
Rated torque : 12.2 kgfm
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3555 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995



Performance : 380 V 50 Hz 2P IE3

Rated current : 67.4 A
LRC : 6.4
Rated torque : 12.3 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 2955 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995



Performance : 400 V 50 Hz 2P IE3

Rated current : 64.0 A
LRC : 7.2
Rated torque : 12.3 kgfm
Locked rotor torque : 220 %
Breakdown torque : 280 %
Rated speed : 2960 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11165995

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE3			
Rated current	: 61.7 A	Moment of inertia (J)	: 0.4485 kgm ²
LRC	: 7.4	Duty cycle	: Cont.(S1)
Rated torque	: 12.2 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.00
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 2965 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995



Performance : 380 V 50 Hz 2P IE1

Rated current : 83.1 A
LRC : 5.2
Rated torque : 14.8 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995



Performance : 400 V 50 Hz 2P IE2

Rated current : 77.6 A
LRC : 5.8
Rated torque : 14.8 kgfm
Locked rotor torque : 180 %
Breakdown torque : 229 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				8 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165995






Performance : 415 V 50 Hz 2P IE2

Rated current : 74.8 A
LRC : 6.3
Rated torque : 14.8 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9Revision		
Checked by				
Date	21/10/2024			



Without vertical jackscrews
Color RAL 5009
Painting plan 203A
Mounting B3R(D)

60 HP 02 Poles 60 Hz										A		
								HYBRISUSER				
											00	
ECM		LOC	SUMMARY OF MODIFICATIONS					EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER		THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 364/5TS IP55 TEFC					PREVIEW WDD 00				
CHECKED												
RELEASED												
REL. DATE												
						SHEET		/				