

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11164579
Catalog # : HT125504NPRBW22

Frame	: 444/5T	Locked rotor time	: 48s (cold) 27s (hot)
Output	: 125 HP	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 111 A	Protection degree	: IP55
L. R. Amperes	: 724 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 36.8 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1785 rpm	Noise level ²	: 73.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 368 ft.lb	Approx. weight ³	: 1590 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 57.2 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	0.000	95.0	95.4	95.4	Max. traction : 1498 lb
Power Factor	0.00	0.74	0.82	0.85	Max. compression : 3011 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.5	3.4	3.0	2.4	1.4	0.9	0.6

	Drive end	Non drive end
Bearing type	: NU-319 C3	: 6316 C3
Sealing	: WSeal	: WSeal
Lubrication interval	: 5000 h	: 10000 h
Lubricant amount	: 45 g	: 34 g
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	03/07/2026			

Page 1 / 6
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11164579

Catalog # : HT125504NPRBW22



Performance : 575 V 60 Hz 4P

Rated current	: 111 A	Moment of inertia (J)	: 57.2 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 368 ft.lb	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 1785 rpm	Design	: B

Locked rotor time : 48s (cold) 27s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	03/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11164579

Catalog # : HT125504NPRBW22



Performance : 575 V 60 Hz 4P

Rated current : 111 A
LRC : 6.5
Rated torque : 368 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 1785 rpm

Moment of inertia (J) : 57.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	03/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11164579

Catalog # : HT125504NPRBW22

Performance : 575 V 60 Hz 4P

Rated current	: 111 A	Moment of inertia (J)	: 57.2 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 368 ft.lb	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 1785 rpm	Design	: B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 6	
Date	03/07/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :



Rev.	Changes Summary		Performed	Checked	Date
Performed by					Page 5 / 6
Checked by					
Date	03/07/2026				
					Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11164579

Catalog # : HT125504NPRBW22



Performance : 575 V 60 Hz 4P

Rated current	: 111 A	Moment of inertia (J)	: 57.2 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 368 ft.lb	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 1785 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 6 / 6		
Checked by				
Date	03/07/2026			
		Revision		

