

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12447101
Catalog # : CT025402NPW22

Frame	: 284/6TSC	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 25 HP (18.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 58.2/29.1 A	Protection degree	: IP55
L. R. Amperes	: 367/183 A	Cooling method	: IC411 - TEFC
LRC	: 6.3x(Code G)	Mounting	: F-1
No load current	: 17.2/8.60 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3550 rpm	Noise level ²	: 72.0 dB(A)
Slip	: 1.39 %	Starting method	: Direct On Line
Rated torque	: 37.0 ft.lb	Approx. weight ³	: 362 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 2.69 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	91.0	91.7	91.7	Max. traction	: 225 lb
Power Factor	0.00	0.77	0.84	0.87	Max. compression	: 592 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.6	6.8	5.9	4.4	2.6	1.7	1.0

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6311 C3	6211 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	14000 h	17000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	

Notes

USABLE @208V 63.0A SF 1.10 SFA 69.3A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 6		
Checked by				
Date	23/07/2026			

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447101

Catalog # : CT025402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 58.2/29.1 A
LRC : 6.3
Rated torque : 37.0 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 3550 rpm

Moment of inertia (J) : 2.69 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 30s (cold) 17s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6Revision		
Checked by				
Date	23/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447101

Catalog # : CT025402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 58.2/29.1 A
LRC : 6.3
Rated torque : 37.0 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 3550 rpm

Moment of inertia (J) : 2.69 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	23/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :					
Product line : W22 NEMA Premium Efficiency Three-Phase		Product code : 12447101 Catalog # : CT025402NPW22			
Performance : 230/460 V 60 Hz 2P					
Rated current : 58.2/29.1 A		Moment of inertia (J) : 2.69 sq.ft.lb			
LRC : 6.3		Duty cycle : Cont.(S1)			
Rated torque : 37.0 ft.lb		Insulation class : F			
Locked rotor torque : 200 %		Service factor : 1.25			
Breakdown torque : 229 %		Temperature rise : 80 K			
Rated speed : 3550 rpm		Design : B			
Heating constant					
Cooling constant					
Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page Revision 4 / 6	
Checked by					
Date	23/07/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	23/07/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447101

Catalog # : CT025402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 58.2/29.1 A
LRC : 6.3
Rated torque : 37.0 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 3550 rpm

Moment of inertia (J) : 2.69 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					

