

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11611205
Catalog # : HT002404NPW22

Frame	: 143/5T	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.72/2.86 A	Protection degree	: IP55
L. R. Amperes	: 47.5/23.7 A	Cooling method	: IC411 - TEFC
LRC	: 8.3x(Code L)	Mounting	: F-1
No load current	: 3.46/1.73 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1750 rpm	Noise level ²	: 51.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 6.00 ft.lb	Approx. weight ³	: 50.7 lb
Locked rotor torque	: 280 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.1561 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	85.0	86.0	86.5	Max. traction	: 170 lb
Power Factor	0.55	0.68	0.76	Max. compression	: 221 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
16.9	13.4	12.0	12.1	8.7	7.9	5.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	00088	

Notes

USABLE @208V 5.85A SF 1.15 SFA 6.73A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/07/2026			

Page 1 / 6
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11611205

Catalog # : HT002404NPW22



Performance : 230/460 V 60 Hz 4P

Rated current : 5.72/2.86 A
LRC : 8.3
Rated torque : 6.00 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 350 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.1561 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 18s (cold) 10s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6Revision		
Checked by				
Date	24/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11611205

Catalog # : HT002404NPW22



Performance : 230/460 V 60 Hz 4P

Rated current : 5.72/2.86 A
LRC : 8.3
Rated torque : 6.00 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 350 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.1561 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	24/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11611205

Catalog # : HT002404NPW22

Performance : 230/460 V 60 Hz 4P

Rated current : 5.72/2.86 A
LRC : 8.3
Rated torque : 6.00 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 350 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.1561 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 4 / 6		Revision
Checked by					
Date	24/07/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	24/07/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11611205

Catalog # : HT002404NPW22



Performance : 230/460 V 60 Hz 4P

Rated current : 5.72/2.86 A
LRC : 8.3
Rated torque : 6.00 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 350 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.1561 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 6	Revision
Checked by					
Date	24/07/2026				

