

NEMA

Model **GRA0402F-TD-01**
MFG PN: T324TS40U2B

Model **GRA0402F-TD-01**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRA0402F-TD-01	40	3550	575	3	60	324TSD	Rigid/D-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRA0402F-TD-01
MFG PN: T324TS40U2B


ELECTRICAL DATA		
Rated Motor Output Power	40	HP
	-	kW
Rated Motor Speed	3550	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	35.80	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	275.55	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	-	@ 50Hz
KVA Code	J	60Hz
	-	50Hz
Nominal Efficiency	92.4	% @ 60Hz
Nominal Power Factor	0.91	cosΦ @ 60Hz
Leads (Qty, Size)	6	10
Connection	D	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	-	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	324TSD	
Enclosure	TEFC	
Mounting	Rigid/D-Flange	
Approximate Weight (lbs.)	366.3 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	1045	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6312 ZZ	
Bearing ODE Side	6212 ZZ	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	91	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRA0402F-TD-01
MFG PN: T324TS40U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	40	40
RPM	3550	-
Voltage	575	-
Full Load Amps	35.80	-
Service Factor	1.25	-
KVA Code	J	-
Full Load Amps (208V)	-	-
Nominal Efficiency	92.4	-
Nominal Power Factor	0.91	-
Design	A	
Frame	324TSD	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6312 ZZ	
Opposite Drive End Bearing	6212 ZZ	
Weight (lbs)	366.3	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR
INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF

MODEL MFG PN

60Hz 50Hz MFG DATE

HP SER #

RPM DESIGN

VOLT FRAME

FLA ENCL / IP TEFC 55

SF DUTY

KVA CODE INS CL

NOM.EFF AMB

EFF 75% DE

PF ODE

USABLE AT 208V WEIGHT lbs

NEMA Premium
TECHTOPCANADA.COM

CLASS 1, DIV 2, GROUPS A, B, C AND D

MADE IN CHINA

CC088A
E323353
C224653
Energy Verified Only

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820



Model GRA0402F-TD-01
MFG PN: T324TS40U2B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	139.1	235	Start Configuration	DOL
Pull-Up Torque	74	125	Starting Current (A)	275.55
Breakdown Torque	139.7	236	No-Load Current (A)	10
Full Load Torque	59.2	100	No-Load Power Factor	-

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	13.5	20.3	28	36.4	45.5	45.5
Efficiency (%)	84.5	90.4	92	92.3	92.1	92.1
Speed (r/min)	3589	3579	3568	3555	3542	3542
Power Factor (cosΦ)	0.66	0.82	0.88	0.9	0.9	0.9
Input Power (kW)	8.88	16.6	24.46	32.49	40.71	40.71


Questions? Call 1.888.286.1820



Model **GRA0402F-TD-01**
MFG PN: T324TS40U2B



Wire	Color
T1, T4	Blue
T5, T2	White
T3, T6	Orange




- NOTES:
- CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - DIAGRAMS FOR REFERENCE ONLY



DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	06/03/25
PREMIUM T-FRAME ALUMINUM MOTORS	



DRAWING NUMBER:	GR3-AL-TF-320TSD-01	ISSUED DATE	06/03/25
DIMENSIONS:	Inches		
MOUNTING:	Rigid/D-Flange	PREMIUM T-FRAME ALUMINUM MOTORS	
CASING MATERIAL:	Cast Aluminum		