

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11455588
Catalog # : HT060508NPRBW22

Frame	: 404/5T	Locked rotor time	: 23s (cold) 13s (hot)
Output	: 60 HP (45 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 58.9 A	Protection degree	: IP55
L. R. Amperes	: 383 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code H)	Mounting	: F-1
No load current	: 19.8 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 875 rpm	Noise level ²	: 60.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 360 ft.lb	Approx. weight ³	: 1111 lb
Locked rotor torque	: 150 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 40.2 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	93.0	93.0	92.4	Max. traction	: 1790 lb
Power Factor	0.68	0.78	0.83	Max. compression	: 2965 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.2	7.4	6.8	3.1	2.4	1.2	0.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	NU-316 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	17000 h	20000 h
Lubricant amount	:	34 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 6 Revision		
Checked by				
Date	06/08/2026			

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11455588

Catalog # : HT060508NPRBW22



Performance : 575 V 60 Hz 8P

Rated current	: 58.9 A	Moment of inertia (J)	: 40.2 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 360 ft.lb	Insulation class	: F
Locked rotor torque	: 150 %	Service factor	: 1.25
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 875 rpm	Design	: B

Locked rotor time : 23s (cold) 13s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	06/08/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11455588

Catalog # : HT060508NPRBW22



Performance : 575 V 60 Hz 8P

Rated current : 58.9 A
LRC : 6.5
Rated torque : 360 ft.lb
Locked rotor torque : 150 %
Breakdown torque : 220 %
Rated speed : 875 rpm

Moment of inertia (J) : 40.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	06/08/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11455588

Catalog # : HT060508NPRBW22

Performance : 575 V 60 Hz 8P

Rated current	: 58.9 A	Moment of inertia (J)	: 40.2 sq.ft.lb
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 360 ft.lb	Insulation class	: F
Locked rotor torque	: 150 %	Service factor	: 1.25
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 875 rpm	Design	: B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	06/08/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	06/08/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11455588

Catalog # : HT060508NPRBW22



Performance : 575 V 60 Hz 8P

Rated current : 58.9 A
LRC : 6.5
Rated torque : 360 ft.lb
Locked rotor torque : 150 %
Breakdown torque : 220 %
Rated speed : 875 rpm

Moment of inertia (J) : 40.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					

