

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 11385484

Frame	: 444/5T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 186/92.8 A	Protection degree	: IP55
L. R. Amperes	: 1039/520 A	Cooling method	: IC411 - TEFC
LRC	: 5.6x(Code F)	Mounting	: F-1
No load current	: 72.0/36.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 885 rpm	Noise level ²	: 63.0 dB(A)
Slip	: 1.67 %	Starting method	: Direct On Line
Rated torque	: 445 ft.lb	Approx. weight ³	: 1444 lb
Locked rotor torque	: 170 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 73.6 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	93.0	93.0	93.0	Max. traction	: 1952 lb
Power Factor	0.67	0.76	0.80	Max. compression	: 3496 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.1	5.7	5.3	3.3	2.2	1.4	1.0

	Drive end	Non drive end
Bearing type	: NU-319 C3	6316 C3
Sealing	: WSeal	WSeal
Lubrication interval	: 15000 h	20000 h
Lubricant amount	: 45 g	34 g
Lubricant type	Mobil Polyrex EM	

Notes

USABLE @208V 205A SF 1.00 SFA 205A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 5		
Checked by				
Date	07/08/2026			
		Revision		


TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 11385484



Performance : 230/460 V 60 Hz 8P

Rated current : 186/92.8 A
LRC : 5.6
Rated torque : 445 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 885 rpm

Moment of inertia (J) : 73.6 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 5 Revision		
Checked by				
Date	07/08/2026			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 11385484



Performance : 230/460 V 60 Hz 8P

Rated current : 186/92.8 A
LRC : 5.6
Rated torque : 445 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 885 rpm

Moment of inertia (J) : 73.6 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 5Revision		
Checked by				
Date	07/08/2026			


THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 11385484



Performance : 230/460 V 60 Hz 8P

Rated current : 186/92.8 A
LRC : 5.6
Rated torque : 445 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 885 rpm

Moment of inertia (J) : 73.6 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 4 / 5Revision		
Checked by				
Date	07/08/2026			


VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase Product code : 11385484



Performance : 230/460 V 60 Hz 8P

Rated current : 186/92.8 A
LRC : 5.6
Rated torque : 445 ft.lb
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 885 rpm

Moment of inertia (J) : 73.6 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 5 / 5Revision			
Checked by					
Date	07/08/2026				

