

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11165996
Catalog # : HT100402NPW22

Frame	: 404/5TS	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 100 HP (75 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 224/112 A	Protection degree	: IP55
L. R. Amperes	: 1456/728 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 52.0/26.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3545 rpm	Noise level ²	: 79.0 dB(A)
Slip	: 1.53 %	Starting method	: Direct On Line
Rated torque	: 148 ft.lb	Approx. weight ³	: 1109 lb
Locked rotor torque	: 240 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 13.2 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	93.0	94.1	94.1	Max. traction	: 601 lb
Power Factor	0.00	0.83	0.88	0.89	Max. compression	: 1710 lb

		Drive end	Non drive end
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	4000 h	4000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes
USABLE @208V 243A SF 1.10 SFA 268A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 6 Revision		
Checked by				
Date	07/08/2026			

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165996

Catalog # : HT100402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 224/112 A
LRC : 6.5
Rated torque : 148 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 260 %
Rated speed : 3545 rpm

Moment of inertia (J) : 13.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 25s (cold) 14s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	07/08/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165996

Catalog # : HT100402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 224/112 A
 LRC : 6.5
 Rated torque : 148 ft.lb
 Locked rotor torque : 240 %
 Breakdown torque : 260 %
 Rated speed : 3545 rpm

Moment of inertia (J) : 13.2 sq.ft.lb
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				3 / 6	
Date					

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165996

Catalog # : HT100402NPW22

Performance : 230/460 V 60 Hz 2P

Rated current : 224/112 A
LRC : 6.5
Rated torque : 148 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 260 %
Rated speed : 3545 rpm

Moment of inertia (J) : 13.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 4 / 6		Revision
Checked by					
Date	07/08/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	07/08/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165996

Catalog # : HT100402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 224/112 A
LRC : 6.5
Rated torque : 148 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 260 %
Rated speed : 3545 rpm

Moment of inertia (J) : 13.2 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					

