

**NEMA**

**Model GRC0156D-TC**  
MFG PN: T284T15U6B

# Model GRC0156D-TC

## Product Data Package



| MODEL       | HP | RPM  | VOLTAGE | PHASE | Hz | FRAME | MOUNT          | ENCLOSURE |
|-------------|----|------|---------|-------|----|-------|----------------|-----------|
| GRC0156D-TC | 15 | 1180 | 230/460 | 3     | 60 | 284TC | Rigid/C-Flange | TEFC      |

### Toronto

**TOLL FREE** 1.888.286.1820  
**PHONE** 905.829.1001  
**EMAIL** info@techtopcanada.com

### Montreal

**TOLL FREE** 1.844.354.5111  
**PHONE** 514.354.1002  
**EMAIL** infoQC@techtopcanada.com

### Moncton


**PHONE** 506.386.5794  
**EMAIL** infoNB@techtopcanada.com

### Winnipeg

**PHONE** 204.633.2779  
**EMAIL** infoMB@techtopcanada.com

### Vancouver

**PHONE** 604.525.1551  
**EMAIL** infoBC@techtopcanada.com



### Index

|                               |     |
|-------------------------------|-----|
| Motor General Data Sheet      | P 2 |
| Nameplate Information         | P 3 |
| Technical Performance Data    | P 4 |
| Motor General Wiring Diagram  | P 5 |
| Motor General Outline Drawing | P 6 |

# NEMA

**Model GRC0156D-TC**  
**MFG PN: T284T15U6B**



| ELECTRICAL DATA                     |              |                            |
|-------------------------------------|--------------|----------------------------|
| Rated Motor Output Power            | 15           | HP                         |
|                                     | -            | kW                         |
| Rated Motor Speed                   | 1180         | r/min 60Hz                 |
|                                     | 970          | r/min 50Hz                 |
| Rated Motor Voltage (+/-10%)        | 230/460      | V/60Hz                     |
|                                     | 190/380      | V/50Hz                     |
| Rated Motor Current                 | 37.8/18.9    | A (I <sub>n</sub> ) @ 60Hz |
|                                     | 45/22.5      | A (I <sub>n</sub> ) @ 50Hz |
| Phase                               | 3            | Ø                          |
| Locked Rotor Current @ High Voltage | 156.9        | A (I <sub>n</sub> ) @ 60Hz |
| FI Current @ 208V                   | 41.82        | A (I <sub>n</sub> ) @ 60Hz |
| Service Factor                      | 1.25         | @ 60Hz                     |
|                                     | 1            | @ 50Hz                     |
| KVA Code                            | L            | 60Hz                       |
|                                     | H            | 50Hz                       |
| Nominal Efficiency                  | 91.7         | % @ 60Hz                   |
| Nominal Power Factor                | 0.81         | cosΦ @ 60Hz                |
| Leads (Qty, Size)                   | 12           | 12                         |
| Connection                          | DD/D         | -                          |
| Coil Resistance                     | 0.559        | Ω                          |
| Start Capacitor                     | -            | µF/V                       |
| Run Capacitor                       | -            | µF/V                       |
| <b>VFD DUTY (S.F. 1.0)</b>          | <b>RATIO</b> | <b>Hz</b>                  |
| Variable Torque                     | 30:1         | 2 - 60                     |
| Constant Torque                     | 15:1         | 4 - 60                     |
| FULL LOAD TEMPERATURE RISE          |              |                            |
| Full Load Temperature Rise          | 41.9         | °C @ 60Hz                  |
|                                     | 57.2         | °C @ 50Hz                  |

| GENERAL DATA                        |                  |           |
|-------------------------------------|------------------|-----------|
| Frame Size                          | 284TC            |           |
| Enclosure                           | TEFC             |           |
| Mounting                            | Rigid/C-Flange   |           |
| Approximate Weight (lbs.)           | 392.9 lbs.       |           |
| Casing Material / Fan Cover         | Cast Iron        | Cast Iron |
| Shaft Material                      | -                |           |
| NEMA Design                         | A                |           |
| Degree of Protection (IP)           | 55               |           |
| Insulation Class / Temp Rise (60Hz) | F                | B         |
| Tropicalization                     | YES              |           |
| Duty                                | Cont. / S1       |           |
| Conduit Box Location                | F1               |           |
| Feet Removable / Double Drilled     | YES              | NO        |
| Paintwork                           | 7024             |           |
|                                     | Graphite Gray    |           |
| MECHANICAL DATA                     |                  |           |
| Bearing DE Side                     | 6311 C3          |           |
| Bearing ODE Side                    | 6311 C3          |           |
| Grease Type                         | Mobil Polyrex EM |           |
| Compensation Ring (wavy washer)     | NDE              |           |
| Moment of Inertia (lb-ft²)          | 5.73             |           |
| Sound Pressure @ 3 FT dBA           | 71.2             |           |
| SITE CONDITIONS                     |                  |           |
| Ambient Temperature (°C)            | 40               |           |
| Meters Above Sea Level (MASL)       | 1000             |           |
| HAZARDOUS LOCATIONS                 |                  |           |
| CSA Certified                       | A, B, C & D      |           |
| Temperature Code                    | T3A              | -         |

**Questions? Call 1.888.286.1820**

**NEMA**

**Model GRC0156D-TC**  
MFG PN: T284T15U6B



| NAMEPLATE DATA             | 60Hz       | 50Hz    |
|----------------------------|------------|---------|
| Horse Power                | 15         | 15      |
| RPM                        | 1180       | 970     |
| Voltage                    | 230/460    | 190/380 |
| Full Load Amps             | 37.8/18.9  | 45/22.5 |
| Service Factor             | 1.25       | 1       |
| KVA Code                   | L          | H       |
| Full Load Amps (208V)      | 41.82      | -       |
| Nominal Efficiency         | 91.7       | 89.8    |
| Nominal Power Factor       | 0.81       | -       |
| Design                     | A          |         |
| Frame                      | 284TC      |         |
| Enclosure Type             | TEFC       |         |
| IP Rating                  | 55         |         |
| Duty                       | Cont. / S1 |         |
| Insulation Class           | F          |         |
| Ambient Rating             | 40         |         |
| Drive End Bearing          | 6311 C3    |         |
| Opposite Drive End Bearing | 6311 C3    |         |
| Weight (lbs)               | 392.9      |         |

NAMEPLATE LAYOUT

|                                                                                       |                          |                     |          |
|---------------------------------------------------------------------------------------|--------------------------|---------------------|----------|
| <b>TECHTOP</b> INDUSTRIAL THREE PHASE MOTOR<br>INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF |                          | TECHTOPCANADA.COM   |          |
| MODEL                                                                                 | 60Hz                     | 50Hz                | MFG PN   |
| NEMA Premium                                                                          | HP                       |                     | MFG DATE |
|                                                                                       | RPM                      |                     | SER #    |
|                                                                                       | VOLT                     |                     | DESIGN   |
|                                                                                       | FLA                      |                     | FRAME    |
|                                                                                       | SF                       |                     | ENCL     |
|                                                                                       | KVA CODE                 |                     | IP       |
|                                                                                       | NOM.EFF                  |                     | DUTY     |
| USABLE AT                                                                             | BEARING SIZE             |                     | INS CL   |
| 208V 60Hz                                                                             | DE                       | ODE                 | AMB      |
| FLA                                                                                   | GREASE: MOBIL POLYREX EM |                     | WEIGHT   |
| MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D                                    |                          | IEEE 45 MARINE DUTY |          |

| VFD DUTY (S.F. 1.0) | RATIO | Hz*    |
|---------------------|-------|--------|
| Variable Torque     | 30:1  | 2 - 60 |
| Constant Torque     | 15:1  | 4 - 60 |

\*For max speed please contact Techtop Canada


| HAZARDOUS LOCATIONS | CSA CERTIFIED   |
|---------------------|-----------------|
| Class / Division    | Class I, Div. 2 |
| Groups              | A, B, C & D     |

Questions? Call 1.888.286.1820



**Model GRC0156D-TC**  
MFG PN: T284T15U6B

**Torque Speed (T-n) Curve**



**PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz**

| TORQUE VALUES       | TORQUE (lb-ft) | TORQUE (% FULL LOAD) | PERFORMANCE VALUES   |       |
|---------------------|----------------|----------------------|----------------------|-------|
| Locked Rotor Torque | 199            | 298                  | Start Configuration  | DOL   |
| Pull-Up Torque      | 135.5          | 203                  | Starting Current (A) | 156.9 |
| Breakdown Torque    | 231            | 346                  | No-Load Current (A)  | 11.4  |
| Full Load Torque    | 66.8           | 100                  | No-Load Power Factor | -     |




**TYPICAL PERFORMANCE - NOT GUARANTEED VALUES**

| % OF RATED LOAD     | 25   | 50   | 75   | 100   | 125   | S.F. 1.25 |
|---------------------|------|------|------|-------|-------|-----------|
| Line Amperes (A)    | 12.2 | 14.1 | 16.8 | 20.1  | 23.9  | 23.9      |
| Efficiency (%)      | 84.1 | 89.9 | 91.3 | 91.4  | 91    | 91        |
| Speed (r/min)       | 1197 | 1193 | 1190 | 1186  | 1182  | 1182      |
| Power Factor (cosΦ) | 0.34 | 0.54 | 0.67 | 0.75  | 0.79  | 0.79      |
| Input Power (kW)    | 3.27 | 6.12 | 9.04 | 12.03 | 15.12 | 15.12     |

Questions? Call 1.888.286.1820



Model **GRC0156D-TC**  
MFG PN: T284T15U6B





- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
  - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
  - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “\*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
  - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
  - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø DD/D 12-Lead Dual Voltage

|                     |                |                                  |          |
|---------------------|----------------|----------------------------------|----------|
| DRAWING NUMBER:     | NEMA-3-12-DD-D | ISSUED DATE                      | 12/05/25 |
| CONNECTION:         | DD/D           | PREMIUM T-FRAME CAST IRON MOTORS |          |
| NUMBER OF LEADS:    | 12             |                                  |          |
| THERMAL PROTECTION: | -              |                                  |          |



NEMA Premium TEFC 284TC

DRAWING NUMBER:

GR3-CI-TF-284TC-CFC

DIMENSIONS:

Inches

MOUNTING:

Rigid/C-Flange

CASING MATERIAL:

Cast Iron

ISSUED DATE

12/05/25

PREMIUM T-FRAME CAST IRON MOTORS