

NEMA

Model GRC0402DS
MFG PN: T286TS40U2B

Model GRC0402DS

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC0402DS	40	3555	230/460	3	60	286TS	Rigid	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC0402DS
MFG PN: T286TS40U2B


ELECTRICAL DATA		
Rated Motor Output Power	40	HP
	-	kW
Rated Motor Speed	3555	r/min 60Hz
	2945	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	91/45.5	A (I _n) @ 60Hz
	110.6/55.3	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	403	A (I _n) @ 60Hz
FI Current @ 208V	101	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	H	60Hz
	H	50Hz
Nominal Efficiency	92.4	% @ 60Hz
Nominal Power Factor	0.89	cosΦ @ 60Hz
Leads (Qty, Size)	12	12
Connection	DD/D	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	65.8	°C @ 60Hz
	66	°C @ 50Hz

GENERAL DATA		
Frame Size	286TS	
Enclosure	TEFC	
Mounting	Rigid	
Approximate Weight (lbs.)	517 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	-	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6311 C3	
Bearing ODE Side	6311 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	91	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRC0402DS
MFG PN: T286TS40U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	40	40
RPM	3555	2945
Voltage	230/460	190/380
Full Load Amps	91/45.5	110.6/55.3
Service Factor	1.25	1
KVA Code	H	H
Full Load Amps (208V)	101	-
Nominal Efficiency	92.4	92.1
Nominal Power Factor	0.89	-
Design	A	
Frame	286TS	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6311 C3	
Opposite Drive End Bearing	6311 C3	
Weight (lbs)	517	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF		TECHTOPCANADA.COM	
MODEL	60Hz	50Hz	MFG PN
NEMA Premium	HP		MFG DATE
	RPM		SER #
	VOLT		DESIGN
	FLA		FRAME
	SF		ENCL
	KVA CODE		IP
	NOM.EFF		DUTY
USABLE AT	BEARING SIZE		INS CL
208V 60Hz	DE	ODE	AMB
FLA	GREASE: MOBIL POLYREX EM		WEIGHT
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC0402DS
MFG PN: T286TS40U2B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	173.7	294	Start Configuration	DOL
Pull-Up Torque	101.1	171	Starting Current (A)	403
Breakdown Torque	175.5	297	No-Load Current (A)	15.1
Full Load Torque	59.1	100	No-Load Power Factor	-


TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	18.4	26.6	35.9	46.1	57.1	57.1
Efficiency (%)	88	92.3	93.3	93.2	92.8	92.8
Speed (r/min)	3592	3584	3575	3565	3554	3554
Power Factor (cosΦ)	0.58	0.77	0.84	0.88	0.89	0.89
Input Power (kW)	8.53	16.25	24.13	32.17	40.41	40.41

Questions? Call **1.888.286.1820**



Model **GRC0402DS**
MFG PN: T286TS40U2B




- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø DD/D 12-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-12-DD-D	ISSUED DATE	28/05/25
CONNECTION:	DD/D	PREMIUM T-FRAME CAST IRON MOTORS	
NUMBER OF LEADS:	12		
THERMAL PROTECTION:	-		



NEMA Premium TEFC 286TS

DRAWING NUMBER:	GR3-CI-TF-286TS-CFC	ISSUED DATE	28/05/25
DIMENSIONS:	Inches	PREMIUM T-FRAME CAST IRON MOTORS	
MOUNTING:	Rigid		
CASING MATERIAL:	Cast Iron		