

NEMA

Model GRC0602F
MFG PN: T364TS60U2B

Model GRC0602F

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC0602F	60	3560	575	3	60	364TS	Rigid	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC0602F
MFG PN: T364TS60U2B




ELECTRICAL DATA		
Rated Motor Output Power	60	HP
	-	kW
Rated Motor Speed	3560	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	53.36	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	536.08	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	-	50Hz
Nominal Efficiency	93.6	% @ 60Hz
Nominal Power Factor	0.9	cosΦ @ 60Hz
Leads (Qty, Size)	6	8
Connection	D	-
Coil Resistance	0.065	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	56.4	°C @ 60Hz
	70	°C @ 50Hz

GENERAL DATA		
Frame Size	364TS	
Enclosure	TEFC	
Mounting	Rigid	
Approximate Weight (lbs.)	794.9 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	-	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	NO
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6313 C3	
Bearing ODE Side	6313 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	7.29	
Sound Pressure @ 3 FT dBA	91.8	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRC0602F
MFG PN: T364TS60U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	60	60
RPM	3560	-
Voltage	575	-
Full Load Amps	53.36	-
Service Factor	1.15	1
KVA Code	K	-
Full Load Amps (208V)	-	-
Nominal Efficiency	93.6	-
Nominal Power Factor	0.9	-
Design	A	
Frame	364TS	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6313 C3	
Opposite Drive End Bearing	6313 C3	
Weight (lbs)	794.9	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF		TECHTOPCANADA.COM	
MODEL	60Hz	50Hz	MFG PN
NEMA Premium	HP		MFG DATE
	RPM		SER #
	VOLT		DESIGN
	FLA		FRAME
	SF		ENCL
	KVA CODE		IP
	NOM.EFF		DUTY
BEARING SIZE		INS CL	
DE	ODE	AMB	WEIGHT
GREASE: MOBIL POLYREX EM		lbs	
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)

Variable Torque
Constant Torque

RATIO

30:1
15:1

Hz*

2 - 60
4 - 60

*For max speed please contact Techtop Canada

HAZARDOUS LOCATIONS

Class / Division
Groups

CSA CERTIFIED


Class I, Div. 2
A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC0602F
MFG PN: T364TS60U2B

Torque Speed (T-n) Curve




PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	262	296	Start Configuration	DOL
Pull-Up Torque	127.5	144	Starting Current (A)	536.08
Breakdown Torque	299.2	338	No-Load Current (A)	18.1
Full Load Torque	88.5	100	No-Load Power Factor	-

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	22.5	31.6	42.4	54.4	67.3	67.3
Efficiency (%)	88.2	92.5	93.6	93.6	93.3	93.3
Speed (r/min)	3593	3585	3576	3568	3558	3558
Power Factor (cosΦ)	0.57	0.77	0.85	0.89	0.9	0.9
Input Power (kW)	12.76	24.32	36.08	48.07	60.31	60.31

Questions? Call 1.888.286.1820



- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY







DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	30/05/25
PREMIUM T-FRAME CAST IRON MOTORS	



Model **GRC0602F**
MFG PN: T364TS60U2B



NEMA Premium TEFC 364TS

DRAWING NUMBER:

GR3-CI-TF-364TS-CFC

DIMENSIONS:

Inches

MOUNTING:

Rigid

CASING MATERIAL:

Cast Iron

ISSUED DATE

30/05/25

PREMIUM T-FRAME CAST IRON MOTORS