

NEMA

Model GRC1004F-RR
MFG PN: T405T100U4B

Model GRC1004F-RR

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC1004F-RR	100	1780	575	3	60	405T	Rigid	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC1004F-RR
MFG PN: T405T100U4B




ELECTRICAL DATA		
Rated Motor Output Power	100	HP
	-	kW
Rated Motor Speed	1780	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	91.30	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	904	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	L	60Hz
	-	50Hz
Nominal Efficiency	95.4	% @ 60Hz
Nominal Power Factor	0.86	cosΦ @ 60Hz
Leads (Qty, Size)	6	6
Connection	D	-
Coil Resistance	0.043	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	70.3	°C @ 60Hz
	100.2	°C @ 50Hz

GENERAL DATA		
Frame Size	405T	
Enclosure	TEFC	
Mounting	Rigid	
Approximate Weight (lbs.)	1063.8 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	-	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	NU 316	
Bearing ODE Side	6314 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	None	
Moment of Inertia (lb-ft²)	20.87	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRC1004F-RR
MFG PN: T405T100U4B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	100	100
RPM	1780	-
Voltage	575	-
Full Load Amps	91.30	-
Service Factor	1.15	1
KVA Code	L	-
Full Load Amps (208V)	-	-
Nominal Efficiency	95.4	-
Nominal Power Factor	0.86	-
Design	A	
Frame	405T	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	NU 316	
Opposite Drive End Bearing	6314 C3	
Weight (lbs)	1063.8	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF		TECHTOPCANADA.COM	
MODEL		MFG PN	
NEMA Premium		MFG DATE	
HP	60Hz 50Hz	SER #	
RPM		DESIGN	
VOLT		FRAME	
FLA		ENCL	
SF		IP	
KVA CODE		DUTY	
NOM.EFF		INS CL	
BEARING SIZE		AMB	
DE	ODE	WEIGHT	
GREASE: MOBIL POLYREX EM			
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC1004F-RR
MFG PN: T405T100U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	979.6	332	Start Configuration	DOL
Pull-Up Torque	292.1	99	Starting Current (A)	904
Breakdown Torque	454.4	154	No-Load Current (A)	33
Full Load Torque	295.1	100	No-Load Power Factor	0.05

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	39	52.5	70.4	91.1	113.1	-
Efficiency (%)	91.8	94.7	95.3	95.1	94.7	-
Speed (r/min)	1796	1792	1788	1783	1778	-
Power Factor (cosΦ)	0.53	0.76	0.84	0.87	0.88	-
Input Power (kW)	20.43	39.58	59.03	78.83	98.97	-

Questions? Call 1.888.286.1820



Model **GRC1004F-RR**
MFG PN: T405T100U4B



- NOTES:
1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 5. DIAGRAMS FOR REFERENCE ONLY






DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	02/06/25
PREMIUM T-FRAME CAST IRON MOTORS	



Model **GRC1004F-RR**
MFG PN: T405T100U4B



NEMA Premium TEFC 405T

DRAWING NUMBER:	GR3-CI-TF-404(5)T-CFC
DIMENSIONS:	Inches
MOUNTING:	Rigid
CASING MATERIAL:	Cast Iron

ISSUED DATE	02/06/25
PREMIUM T-FRAME CAST IRON MOTORS	