

NEMA

Model GRC1504E-RR
MFG PN: T445T 150U4B

Model GRC1504E-RR

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC1504E-RR	150	1785	460	3	60	445T	Rigid	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC1504E-RR
MFG PN: T445T 150U4B


ELECTRICAL DATA		
Rated Motor Output Power	150	HP
	-	kW
Rated Motor Speed	1785	r/min 60Hz
	1480	r/min 50Hz
Rated Motor Voltage (+/-10%)	460	V/60Hz
	380	V/50Hz
Rated Motor Current	165.00	A (I _n) @ 60Hz
	198.00	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	1544	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	0	60Hz
	H	50Hz
Nominal Efficiency	95.8	% @ 60Hz
Nominal Power Factor	0.89	cosΦ @ 60Hz
Leads (Qty, Size)	6	2
Connection	D	-
Coil Resistance	15	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	71.7	°C @ 60Hz
	108.7	°C @ 50Hz

GENERAL DATA		
Frame Size	445T	
Enclosure	TEFC	
Mounting	Rigid	
Approximate Weight (lbs.)	1685.2 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	4140	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	NU 319	
Bearing ODE Side	6319 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	None	
Moment of Inertia (lb-ft²)	55.54	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRC1504E-RR
MFG PN: T445T 150U4B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	150	150
RPM	1785	1480
Voltage	460	380
Full Load Amps	165.00	198.00
Service Factor	1.15	1
KVA Code	0	H
Full Load Amps (208V)	-	-
Nominal Efficiency	95.8	95
Nominal Power Factor	0.89	-
Design	A	
Frame	445T	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	NU 319	
Opposite Drive End Bearing	6319 C3	
Weight (lbs)	1685.2	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF		TECHTOPCANADA.COM	
MODEL		MFG PN	
NEMA Premium	60Hz 50Hz	MFG DATE	
HP		SER #	
RPM		DESIGN	
VOLT		FRAME	
FLA		ENCL	
SF		IP	
KVA CODE		DUTY	
NOM.EFF		INS CL	
USABLE AT 208V 60Hz		AMB	
FLA		WEIGHT	
BEARING SIZE		lbs	
DE	ODE		
GREASE: MOBIL POLYREX EM		Energy Verified	
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)

Variable Torque
Constant Torque

RATIO

30:1
15:1

Hz*

2 - 60
4 - 60

*For max speed please contact Techtop Canada

HAZARDOUS LOCATIONS

Class / Division
Groups

CSA CERTIFIED


Class I, Div. 2
A, B, C & D

Questions? Call 1.888.286.1820



Model GRC1504E-RR
MFG PN: T445T 150U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)
Locked Rotor Torque	1368.2	310
Pull-Up Torque	618.1	140
Breakdown Torque	1637.4	371
Full Load Torque	441.3	100

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES


PERFORMANCE VALUES	
Start Configuration	DOL
Starting Current (A)	1544
No-Load Current (A)	49.2
No-Load Power Factor	0.05

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	63	91.8	125.8	163.5	203.3	186.9
Efficiency (%)	93.1	95.5	96	95.8	95.5	95.5
Speed (r/min)	1797	1794	1791	1787	1784	1785
Power Factor (cosΦ)	0.6	0.8	0.87	0.9	0.91	0.9
Input Power (kW)	30.07	58.61	87.52	116.85	146.61	134.68

Questions? Call 1.888.286.1820



Model **GRC1504E-RR**
MFG PN: T445T 150U4B



SINGLE VOLTAGE

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY




DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	06/06/25
PREMIUM T-FRAME CAST IRON MOTORS	



Model **GRC1504E-RR**
MFG PN: T445T 150U4B



NEMA Premium TEFC 445T

DRAWING NUMBER:	GR3-CI-TF-444(5)T-CFC	ISSUED DATE	06/06/25
DIMENSIONS:	Inches	PREMIUM T-FRAME CAST IRON MOTORS	
MOUNTING:	Rigid		
CASING MATERIAL:	Cast Iron		