

NEMA

Model GRC2502F-TC
MFG PN: T449T 250U2B

Model GRC2502F-TC

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC2502F-TC	250	3570	575	3	60	449TSC	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC2502F-TC
MFG PN: T449T 250U2B

ELECTRICAL DATA		
Rated Motor Output Power	250	HP
	-	kW
Rated Motor Speed	3570	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	212.47	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	1737.6	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	-	50Hz
Nominal Efficiency	95.8	% @ 60Hz
Nominal Power Factor	0.9	cosΦ @ 60Hz
Leads (Qty, Size)	6	2
Connection	D	-
Coil Resistance	14.1	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	75.3	°C @ 60Hz
	100.3	°C @ 50Hz

GENERAL DATA		
Frame Size	449TSC	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	2077 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	4140	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6316 C3	
Bearing ODE Side	6316 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	38.67	
Sound Pressure @ 3 FT dBA	96.1	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-



Questions? Call 1.888.286.1820

DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR
PREMIUM T-FRAME CAST IRON MOTORS



NEMA

Model GRC2502F-TC
MFG PN: T449T 250U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	250	250
RPM	3570	-
Voltage	575	-
Full Load Amps	212.47	-
Service Factor	1.15	1
KVA Code	K	-
Full Load Amps (208V)	-	-
Nominal Efficiency	95.8	-
Nominal Power Factor	0.9	-
Design	A	
Frame	449TSC	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6316 C3	
Opposite Drive End Bearing	6316 C3	
Weight (lbs)	2077	

NAMEPLATE LAYOUT

		INDUSTRIAL THREE PHASE MOTOR	
		INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF	
MODEL	TECHTOPCANADA.COM		
NEMA Premium	60Hz	50Hz	MFG PN
HP			MFG DATE
RPM			SER #
VOLT			DESIGN
FLA			FRAME
SF			ENCL
KVA CODE			IP
NOM.EFF			DUTY
			INS CL
			AMB
			WEIGHT
			lbs
			Energy Verified Only
			IEEE 45 MARINE DUTY
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D			

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC2502F-TC
MFG PN: T449T 250U2B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	1040.8	283	Start Configuration	DOL
Pull-Up Torque	529.6	144	Starting Current (A)	1737.6
Breakdown Torque	1099.7	299	No-Load Current (A)	18.1
Full Load Torque	367.8	100	No-Load Power Factor	-

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	28.1	45.4	64.5	84.9	106.3	97.6
Efficiency (%)	93.3	93.3	95.8	95.6	95.1	95.1
Speed (r/min)	3593	3587	3580	3573	3564	3564
Power Factor (cosΦ)	0.78	0.89	0.92	0.93	0.92	0.92
Input Power (kW)	49.99	97.64	145.99	195.13	245.13	245.13


Questions? Call 1.888.286.1820



Model **GRC2502F-TC**
MFG PN: T449T 250U2B



Wire	Color
T1, T4	Blue
T5, T2	White
T3, T6	Orange



SINGLE VOLTAGE

- NOTES:
1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 5. DIAGRAMS FOR REFERENCE ONLY




DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	06/06/25
PREMIUM T-FRAME CAST IRON MOTORS	



Model **GRC2502F-TC**
MFG PN: T449T 250U2B



NEMA Premium TEFC 449TSC

DRAWING NUMBER:	GR3-CI-TF-447(9)TSC-CFC	ISSUED DATE	06/06/25
DIMENSIONS:	Inches	PREMIUM T-FRAME CAST IRON MOTORS	
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Cast Iron		