

**NEMA**

**Model DPA0022F**  
MFG PN: TDA145T2U2B

# Model DPA0022F

## Product Data Package



| MODEL    | HP | RPM  | VOLTAGE | PHASE | Hz | FRAME | MOUNT | ENCLOSURE |
|----------|----|------|---------|-------|----|-------|-------|-----------|
| DPA0022F | 2  | 3510 | 575     | 3     | 60 | 145T  | Rigid | ODP       |

### Toronto

**TOLL FREE** 1.888.286.1820  
**PHONE** 905.829.1001  
**EMAIL** info@techtopcanada.com

### Montreal

**TOLL FREE** 1.844.354.5111  
**PHONE** 514.354.1002  
**EMAIL** infoQC@techtopcanada.com

### Moncton


**PHONE** 506.386.5794  
**EMAIL** infoNB@techtopcanada.com

### Winnipeg

**PHONE** 204.633.2779  
**EMAIL** infoMB@techtopcanada.com

### Vancouver

**PHONE** 604.525.1551  
**EMAIL** infoBC@techtopcanada.com



### Index

|                               |     |
|-------------------------------|-----|
| Motor General Data Sheet      | P 2 |
| Nameplate Information         | P 3 |
| Technical Performance Data    | P 4 |
| Motor General Wiring Diagram  | P 5 |
| Motor General Outline Drawing | P 6 |



**Model DPA0022F**  
 MFG PN: TDA145T2U2B


| ELECTRICAL DATA                     |       |                            |
|-------------------------------------|-------|----------------------------|
| Rated Motor Output Power            | 2     | HP                         |
|                                     | 1.5   | kW                         |
| Rated Motor Speed                   | 3510  | r/min 60Hz                 |
|                                     | -     | r/min 50Hz                 |
| Rated Motor Voltage (+/-10%)        | 575   | V/60Hz                     |
|                                     | -     | V/50Hz                     |
| Rated Motor Current                 | 2.15  | A (I <sub>n</sub> ) @ 60Hz |
|                                     | -     | A (I <sub>n</sub> ) @ 50Hz |
| Phase                               | 3     | Ø                          |
| Locked Rotor Current @ High Voltage | -     | A (I <sub>n</sub> ) @ 60Hz |
| FI Current @ 208V                   | -     | A (I <sub>n</sub> ) @ 60Hz |
| Service Factor                      | 1.25  | @ 60Hz                     |
|                                     | -     | @ 50Hz                     |
| KVA Code                            | L     | 60Hz                       |
|                                     | -     | 50Hz                       |
| Nominal Efficiency                  | 85.5  | % @ 60Hz                   |
| Nominal Power Factor                | 0.82  | cosΦ @ 60Hz                |
| Leads (Qty, Size)                   | 3     | 18                         |
| Connection                          | Y     | -                          |
| Coil Resistance                     | -     | Ω                          |
| Start Capacitor                     | -     | µF/V                       |
| Run Capacitor                       | -     | µF/V                       |
| VFD DUTY (S.F. 1.0)                 | RATIO | Hz                         |
| Variable Torque                     | 30:1  | 2 - 60                     |
| Constant Torque                     | 15:1  | 4 - 60                     |
| FULL LOAD TEMPERATURE RISE          |       |                            |
| Full Load Temperature Rise          | -     | °C @ 60Hz                  |
|                                     | -     | °C @ 50Hz                  |

| GENERAL DATA                        |                  |       |
|-------------------------------------|------------------|-------|
| Frame Size                          | 145T             |       |
| Enclosure                           | ODP              |       |
| Mounting                            | Rigid            |       |
| Approximate Weight (lbs.)           | 27.8 lbs.        |       |
| Casing Material / Fan Cover         | Cast Aluminum    | Steel |
| Shaft Material                      | 1045             |       |
| NEMA Design                         | B                |       |
| Degree of Protection (IP)           | 23               |       |
| Insulation Class / Temp Rise (60Hz) | F                | B     |
| Tropicalization                     | YES              |       |
| Duty                                | Cont. / S1       |       |
| Conduit Box Location                | F1               |       |
| Feet Removable / Double Drilled     | YES              | YES   |
| Paintwork                           | 7024             |       |
|                                     | Graphite Gray    |       |
| MECHANICAL DATA                     |                  |       |
| Bearing DE Side                     | 6205 ZZ          |       |
| Bearing ODE Side                    | 6205 ZZ          |       |
| Grease Type                         | Mobil Polyrex EM |       |
| Compensation Ring (wavy washer)     | NDE              |       |
| Moment of Inertia (lb-ft²)          | -                |       |
| Sound Pressure @ 3 FT dBA           | -                |       |
| SITE CONDITIONS                     |                  |       |
| Ambient Temperature (°C)            | 40               |       |
| Meters Above Sea Level (MASL)       | 1000             |       |
| HAZARDOUS LOCATIONS                 |                  |       |
| CSA Certified                       | -                |       |
| Temperature Code                    | -                | -     |

Questions? Call 1.888.286.1820

**NEMA**

**Model DPA0022F**  
 MFG PN: TDA145T2U2B



| NAMEPLATE DATA             | 60Hz       | 50Hz |
|----------------------------|------------|------|
| Horse Power                | 2          | -    |
| RPM                        | 3510       | -    |
| Voltage                    | 575        | -    |
| Full Load Amps             | 2.15       | -    |
| Service Factor             | 1.25       | -    |
| KVA Code                   | L          | -    |
| Full Load Amps (208V)      | -          | -    |
| Nominal Efficiency         | 85.5       | -    |
| Nominal Power Factor       | 0.82       | -    |
| Design                     | B          |      |
| Frame                      | 145T       |      |
| Enclosure Type             | ODP        |      |
| IP Rating                  | 23         |      |
| Duty                       | Cont. / S1 |      |
| Insulation Class           | F          |      |
| Ambient Rating             | 40         |      |
| Drive End Bearing          | 6205 ZZ    |      |
| Opposite Drive End Bearing | 6205 ZZ    |      |
| Weight (lbs)               | 27.8       |      |

**NAMEPLATE LAYOUT**

**TECHTOP** INDUSTRIAL THREE PHASE MOTOR  
 INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF

MODEL  MFG PN

60Hz 50Hz

HP  MFG DATE

RPM  SER #

VOLT  DESIGN

FLA  FRAME

SF  ENCL / IP ODP 23

KVA CODE  DUTY

NOM.EFF  INS CL

EFF 75%  AMB

PF  DE

USABLE AT 208V  ODE

**NEMA Premium**  WEIGHT

TECHTOPCANADA.COM

MADE IN CHINA

| VFD DUTY (S.F. 1.0) | RATIO | Hz*    |
|---------------------|-------|--------|
| Variable Torque     | 30:1  | 2 - 60 |
| Constant Torque     | 15:1  | 4 - 60 |

\*For max speed please contact Techtop Canada


| HAZARDOUS LOCATIONS | - |
|---------------------|---|
| Class / Division    | - |
| Groups              | - |

**Questions? Call 1.888.286.1820**

**NEMA**

**Model DPA0022F**  
MFG PN: TDA145T2U2B

**Torque Speed (T-n) Curve**



**PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz**

| TORQUE VALUES       | TORQUE (lb-ft) | TORQUE (% FULL LOAD) | PERFORMANCE VALUES   |     |
|---------------------|----------------|----------------------|----------------------|-----|
| Locked Rotor Torque | 3              | 310                  | Start Configuration  | DOL |
| Pull-Up Torque      | 8.7            | 290                  | Starting Current (A) | -   |
| Breakdown Torque    | 12.3           | 410                  | No-Load Current (A)  | -   |
| Full Load Torque    | 9.3            | 100                  | No-Load Power Factor | -   |


**TYPICAL PERFORMANCE - NOT GUARANTEED VALUES**

| % OF RATED LOAD     | 25 | 50   | 75   | 100  | 125 | S.F. 1.25 |
|---------------------|----|------|------|------|-----|-----------|
| Line Amperes (A)    | -  | -    | -    | -    | -   | -         |
| Efficiency (%)      | -  | 81.5 | 84.5 | 85.5 | -   | -         |
| Speed (r/min)       | -  | -    | -    | -    | -   | -         |
| Power Factor (cosΦ) | -  | 0.6  | 0.73 | 0.82 | -   | -         |
| Input Power (kW)    | -  | -    | -    | -    | -   | -         |

Questions? **Call 1.888.286.1820**



Model **DPA0022F**  
MFG PN: TDA145T2U2B




- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
  - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
  - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “\*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
  - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
  - 5. DIAGRAMS FOR REFERENCE ONLY



|                     |            |
|---------------------|------------|
| DRAWING NUMBER:     | NEMA-3-3-Y |
| CONNECTION:         | Y          |
| NUMBER OF LEADS:    | 3          |
| THERMAL PROTECTION: | -          |

**NEMA 3Ø Y 3-Lead Single Voltage**

|                                                  |          |
|--------------------------------------------------|----------|
| ISSUED DATE                                      | 09/06/25 |
| PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP |          |



NEMA Premium ODP 145T

|                  |                   |                                                  |          |
|------------------|-------------------|--------------------------------------------------|----------|
| DRAWING NUMBER:  | GR3-AL-DP-143(5)T | ISSUED DATE                                      | 09/06/25 |
| DIMENSIONS:      | Inches            | PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP |          |
| MOUNTING:        | Rigid             |                                                  |          |
| CASING MATERIAL: | Cast Aluminum     |                                                  |          |