

NEMA

Model DPA0024D
MFG PN: TDA145T2U4B

Model DPA0024D

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
DPA0024D	2	1740	230/460	3	60	145T	Rigid	ODP

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model DPA0024D
 MFG PN: TDA145T2U4B


ELECTRICAL DATA		
Rated Motor Output Power	2	HP
	1.5	kW
Rated Motor Speed	1740	r/min 60Hz
	1420	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	5.80/2.90	A (I _n) @ 60Hz
	6.74/3.37	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	-	A (I _n) @ 60Hz
FI Current @ 208V	6.42	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	H	50Hz
Nominal Efficiency	86.5	% @ 60Hz
Nominal Power Factor	0.75	cosΦ @ 60Hz
Leads (Qty, Size)	9	18
Connection	YY/Y	-
Coil Resistance	-	Ω
Start Capacitor	-	μF/V
Run Capacitor	-	μF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	-	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	145T	
Enclosure	ODP	
Mounting	Rigid	
Approximate Weight (lbs.)	36.7 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	1045	
NEMA Design	B	
Degree of Protection (IP)	23	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6205 ZZ	
Bearing ODE Side	6205 ZZ	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call **1.888.286.1820**

NEMA

Model DPA0024D
 MFG PN: TDA145T2U4B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	2	2
RPM	1740	1420
Voltage	230/460	190/380
Full Load Amps	5.80/2.90	6.74/3.37
Service Factor	1.25	1
KVA Code	K	H
Full Load Amps (208V)	6.42	-
Nominal Efficiency	86.5	83.5
Nominal Power Factor	0.75	0.81
Design	B	
Frame	145T	
Enclosure Type	ODP	
IP Rating	23	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6205 ZZ	
Opposite Drive End Bearing	6205 ZZ	
Weight (lbs)	36.7	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR
 INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF

MODEL	60Hz	50Hz	MFG PN	
HP			MFG DATE	
RPM			SER #	
VOLT			DESIGN	
FLA			FRAME	
SF			ENCL / IP	ODP 23
KVA CODE			DUTY	
NOM.EFF			INS CL	
EFF 75%			AMB	
PF			DE	
USABLE AT 208V			ODE	
	A		WEIGHT	lbs

NEMA Premium
 TECHTOPCANADA.COM

MADE IN CHINA

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	
Class / Division	-
Groups	-

Questions? Call 1.888.286.1820

NEMA

Model DPA0024D
MFG PN: TDA145T2U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	6	330	Start Configuration	DOL
Pull-Up Torque	19.3	320	Starting Current (A)	-
Breakdown Torque	23.6	390	No-Load Current (A)	-
Full Load Torque	19.9	100	No-Load Power Factor	-



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	-	-	-	-	-	-
Efficiency (%)	-	85.5	87	86.5	-	-
Speed (r/min)	-	-	-	-	-	-
Power Factor (cosΦ)	-	0.53	0.67	0.75	-	-
Input Power (kW)	-	-	-	-	-	-


Questions? **Call 1.888.286.1820**



Model **DPA0024D**
MFG PN: TDA145T2U4B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y	ISSUED DATE	09/06/25
CONNECTION:	YY/Y	PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



NEMA Premium ODP 145T

DRAWING NUMBER:	GR3-AL-DP-143(5)T	ISSUED DATE	09/06/25
DIMENSIONS:	Inches	PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	
MOUNTING:	Rigid		
CASING MATERIAL:	Cast Aluminum		