

NEMA

Model DPA0156F-TC
MFG PN: TDA 284T15U6B

Model DPA0156F-TC

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
DPA0156F-TC	15	1180	575	3	60	284TC	Rigid/C-Flange	ODP

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6



Model DPA0156F-TC
 MFG PN: TDA 284T15U6B


ELECTRICAL DATA		
Rated Motor Output Power	15	HP
	11	kW
Rated Motor Speed	1180	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	15.71	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	138.64	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	-	@ 50Hz
KVA Code	K	60Hz
	-	50Hz
Nominal Efficiency	91.7	% @ 60Hz
Nominal Power Factor	0.78	cosΦ @ 60Hz
Leads (Qty, Size)	6	12
Connection	D	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	35.9	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	284TC	
Enclosure	ODP	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	297 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	1045	
NEMA Design	B	
Degree of Protection (IP)	23	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6311 C3	
Bearing ODE Side	6311 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820

NEMA

Model DPA0156F-TC
 MFG PN: TDA 284T15U6B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	15	-
RPM	1180	-
Voltage	575	-
Full Load Amps	15.71	-
Service Factor	1.25	-
KVA Code	K	-
Full Load Amps (208V)	-	-
Nominal Efficiency	91.7	-
Nominal Power Factor	0.78	-
Design	B	
Frame	284TC	
Enclosure Type	ODP	
IP Rating	23	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6311 C3	
Opposite Drive End Bearing	6311 C3	
Weight (lbs)	297	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE MOTOR
 INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF

MODEL MFG PN
 60Hz 50Hz MFG DATE
 HP RPM SER #
 VOLT DESIGN
 FLA FRAME
 SF ENCL / IP ODP 23
 KVA CODE DUTY
 NOM.EFF INS CL
 EFF 75% AMB
 PF DE
 USABLE AT 208V ODE
 A WEIGHT lbs

NEMA Premium
 TECHTOPCANADA.COM

MADE IN CHINA

VFD DUTY (S.F. 1.0)

Variable Torque
 Constant Torque

RATIO

30:1
 15:1

Hz*

2 - 60
 4 - 60

*For max speed please contact Techtop Canada

HAZARDOUS LOCATIONS

Class / Division
 Groups


-
 -
 -

Questions? Call 1.888.286.1820

NEMA

Model DPA0156F-TC
MFG PN: TDA 284T15U6B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	66.8	318	Start Configuration	DOL
Pull-Up Torque	141.6	212	Starting Current (A)	138.64
Breakdown Torque	227.8	341	No-Load Current (A)	9.4
Full Load Torque	212.4	100	No-Load Power Factor	-

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	9.8	11.5	13.6	16.3	19.2	19.2
Efficiency (%)	83	89.3	91	91.3	91	91
Speed (r/min)	1197	1194	1191	1187	1184	1184
Power Factor (cosΦ)	0.34	0.54	0.67	0.74	0.79	0.79
Input Power (kW)	3.31	6.16	9.07	12.05	15.11	15.11

Questions? Call 1.888.286.1820



HIGH VOLTAGE
(Δ)



LOW VOLTAGE
(ΔΔ)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



DRAWING NUMBER:	NEMA-3-12-DD-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-

NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	20/06/25
PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	

MFG PN: TDA 284T15U6B



PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP