

NEMA

Model DPC0406D
MFG PN: TDC 364T40U6B

Model DPC0406D

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
DPC0406D	40	1185	230/460	3	60	364T	Rigid	ODP

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA


Model DPC0406D
 MFG PN: TDC 364T40U6B

ELECTRICAL DATA		
Rated Motor Output Power	40	HP
	30	kW
Rated Motor Speed	1185	r/min 60Hz
	980	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	92.56/46.28	A (I _n) @ 60Hz
	111.64/55.82	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	814.53	A (I _n) @ 60Hz
FI Current @ 208V	102.35	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	G	50Hz
Nominal Efficiency	94.1	% @ 60Hz
Nominal Power Factor	0.86	cosΦ @ 60Hz
Leads (Qty, Size)	12	8
Connection	DD/D	—
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	30.1	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	364T	
Enclosure	ODP	
Mounting	Rigid	
Approximate Weight (lbs.)	725 lbs.	
Casing Material / Fan Cover	Cast Iron	-
Shaft Material	1045	
NEMA Design	A	
Degree of Protection (IP)	23	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6313 C3	
Bearing ODE Side	6313 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820

Model DPC0406D
MFG PN: TDC 364T40U6B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	40	40
RPM	1185	980
Voltage	230/460	190/380
Full Load Amps	92.56/46.28	111.64/55.82
Service Factor	1.15	1
KVA Code	K	G
Full Load Amps (208V)	102.35	-
Nominal Efficiency	94.1	92.3
Nominal Power Factor	0.86	0.88
Design	A	
Frame	364T	
Enclosure Type	ODP	
IP Rating	23	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6313 C3	
Opposite Drive End Bearing	6313 C3	
Weight (lbs)	725	

NAMEPLATE LAYOUT

TECHTOP		INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF					
		TECHTOPCANADA.COM					
MODEL							
 HP RPM VOLT FLA SF KVA CODE NOM.EFF	60Hz		50Hz				
USABLE AT 208V 60Hz <table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 50%; height: 30px;"></td><td style="width: 50%; height: 30px;"></td></tr></table>				BEARING SIZE <table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 50%; height: 30px; text-align: center;">DE</td><td style="width: 50%; height: 30px; text-align: center;">ODE</td></tr></table> GREASE: MOBIL POLYREX EM		DE	ODE
DE	ODE						
<table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 50%; height: 30px; text-align: center;">FLA</td><td style="width: 50%; height: 30px;"></td></tr></table>		FLA		MFG PN MFG DATE SER # DESIGN FRAME ENCL IP DUTY INS CL AMB WEIGHT			
FLA							
		 CC096A C US 224693 Energy Verified Only					
MADE IN CHINA							

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	-
Class / Division	-
Groups	-

Questions? Call 1.888.286.1820

NEMA

Model DPC0406D
MFG PN: TDC 364T40U6B

Torque Speed (T-n) Curve





PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	493.1	278	Start Configuration	DOL
Pull-Up Torque	379.6	214	Starting Current (A)	814.53
Breakdown Torque	562.2	317	No-Load Current (A)	20.2
Full Load Torque	177.4	100	No-Load Power Factor	-


TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	23	29.6	38	47.8	58.5	58.5
Efficiency (%)	90.1	93.7	94.5	94.4	94	94
Speed (r/min)	1197	1195	1192	1189	1186	1186
Power Factor (cosΦ)	0.46	0.68	0.79	0.83	0.86	0.86
Input Power (kW)	8.33	16.01	23.82	31.77	39.89	39.89

Questions? **Call 1.888.286.1820**



HIGH VOLTAGE
(Δ)



LOW VOLTAGE
($\Delta\Delta$)

NOTES:



1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
5. DIAGRAMS FOR REFERENCE ONLY



DRAWING NUMBER:	NEMA-3-12-DD-D	ISSUED DATE	23/06/25
CONNECTION:	DD/D		
NUMBER OF LEADS:	12	PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	
THERMAL PROTECTION:	-		

NEMA

Model DPC0406D
MFG PN: TDC 364T40U6B



NEMA Premium ODP 364T

DRAWING NUMBER:

GR3-CI-DP-364(5)T

DIMENSIONS:

Inches

MOUNTING:

Rigid

CASING MATERIAL:

Cast Iron

ISSUED DATE

23/06/25

PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP