

NEMA

Model DPC0752D
MFG PN: TDC 364TS75U2B

Model DPC0752D

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
DPC0752D	75	3560	230/460	3	60	364TS	Rigid	ODP

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6



Model DPC0752D
 MFG PN: TDC 364TS75U2B



ELECTRICAL DATA		
Rated Motor Output Power	75	HP
	55	kW
Rated Motor Speed	3560	r/min 60Hz
	2950	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	166.73/83.37	A (I _n) @ 60Hz
	203.13/101.57	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	612.6	A (I _n) @ 60Hz
FI Current @ 208V	184.36	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	J	60Hz
	G	50Hz
Nominal Efficiency	93.6	% @ 60Hz
Nominal Power Factor	0.9	cosΦ @ 60Hz
Leads (Qty, Size)	12	8
Connection	DD/D	—
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	40.2	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	364TS	
Enclosure	ODP	
Mounting	Rigid	
Approximate Weight (lbs.)	650 lbs.	
Casing Material / Fan Cover	Cast Iron	-
Shaft Material	1045	
NEMA Design	A	
Degree of Protection (IP)	23	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6313 C3	
Bearing ODE Side	6313 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820

NEMA

Model DPC0752D
 MFG PN: TDC 364TS75U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	75	75
RPM	3560	2950
Voltage	230/460	190/380
Full Load Amps	166.73/83.37	203.13/101.57
Service Factor	1.15	1
KVA Code	J	G
Full Load Amps (208V)	184.36	-
Nominal Efficiency	93.6	93
Nominal Power Factor	0.9	0.9
Design	A	
Frame	364TS	
Enclosure Type	ODP	
IP Rating	23	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6313 C3	
Opposite Drive End Bearing	6313 C3	
Weight (lbs)	650	

NAMEPLATE LAYOUT

TECHTOP		INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF	
MODEL		TECHTOPCANADA.COM	
NEMA Premium		60Hz	50Hz
HP		MFG PN	
RPM		MFG DATE	
VOLT		SER #	
FLA		DESIGN	
SF		FRAME	
KVA CODE		ENCL	
NOM.EFF		IP	
USABLE AT 208V 60Hz		DUTY	
FLA		INS CL	
		AMB	
		WEIGHT	lbs
MADE IN CHINA		CC098A C224683 Energy Verified Only	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	
Class / Division	-
Groups	-

Questions? Call 1.888.286.1820

NEMA

Model DPC0752D
MFG PN: TDC 364TS75U2B

Torque Speed (T-n) Curve




PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	242.4	219	Start Configuration	DOL
Pull-Up Torque	153.9	139	Starting Current (A)	612.6
Breakdown Torque	326.6	295	No-Load Current (A)	23.4
Full Load Torque	110.7	100	No-Load Power Factor	-


TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	30.5	44.8	61.2	79.4	99	99
Efficiency (%)	88.9	92.9	93.8	93.7	93.3	93.3
Speed (r/min)	3592	3583	3574	3565	3554	3554
Power Factor (cosΦ)	0.61	0.8	0.87	0.89	0.9	0.9
Input Power (kW)	15.47	29.6	43.99	58.67	73.68	73.68

Questions? **Call 1.888.286.1820**



HIGH VOLTAGE
(Δ)




LOW VOLTAGE
(ΔΔ)

- NOTES:
1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 5. DIAGRAMS FOR REFERENCE ONLY



 TECHTOP <i>You can't top a Techtop.</i>		NEMA 3Ø DD/D 12-Lead Dual Voltage	
DRAWING NUMBER:	NEMA-3-12-DD-D	ISSUED DATE	27/06/25
CONNECTION:	DD/D		
NUMBER OF LEADS:	12	PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	
THERMAL PROTECTION:	-		

NEMA 3Ø DD/D 12-Lead Dual Voltage



NEMA Premium ODP 364TS

DRAWING NUMBER:	GR3-CI-DP-364(5)TS	ISSUED DATE	27/06/25
DIMENSIONS:	Inches	PREMIUM T-FRAME ALUMINUM & CAST IRON MOTORS, ODP	
MOUNTING:	Rigid		
CASING MATERIAL:	Cast Iron		