

NEMA

Model GPS0022C-C-RND-01
MFG PN: SLF56H2Z2L

Model **GPS0022C-C-RND-01**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GPS0022C-C-RND-01	2	3460	115/208-230	1	60	56HC	Round Body/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton

PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6




Model GPS0022C-C-RND-01
MFG PN: SLF56H2Z2L

ELECTRICAL DATA		
Rated Motor Output Power	2	HP
	-	kW
Rated Motor Speed	3460	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	115/208-230	V/60Hz
	-	V/50Hz
Rated Motor Current	18.2/10.0-9.1	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	1	Ø
Locked Rotor Current @ High Voltage	61.02	A (I _n) @ 60Hz
FI Current @ 208V	10	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	-	@ 50Hz
KVA Code	J	60Hz
	-	50Hz
Nominal Efficiency	77	% @ 60Hz
Nominal Power Factor	0.93	cosΦ @ 60Hz
Leads (Qty, Size)	6	14
Connection	-	-
Coil Resistance	-	Ω
Start Capacitor	500/165	µF/V
Run Capacitor	115/250	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	-	-
Constant Torque	-	-
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	55	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	56HC	
Enclosure	TEFC	
Mounting	Round Body/C-Flange	
Approximate Weight (lbs.)	43 lbs.	
Casing Material / Fan Cover	Rolled Steel	Steel
Shaft Material	1045	
NEMA Design	L	
Degree of Protection (IP)	54	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	NO	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	-	-
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6204 2RS	
Bearing ODE Side	6203 2RS	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820

MFG PN: SLF56H2Z2L



NAMEPLATE LAYOUT

	TECHTOP	Date of Mfg: SER No.
GEN. PURPOSE SINGLE PHASE MOTOR		
MODEL:	MFG PN:SLF	
FRAME: 	HP: 	RPM:
VOLTS: 	HZ: 	AMPS:
KVA Code: 	PF: 	EFF:
DUTY: 		
DES: 	INS.CLASS: 	
AMBIENT: 		
40 °C		
ENCL: 	CAP: 	μF
V		
DE. BRG: 	ZZ	
ODE. BRG: 		
ZZ		
WIRING DIAGRAM		

*For max speed please contact Techtop Canada

Questions? Call 1.888.286.1820





NEMA

Model GPS0022C-C-RND-01
MFG PN: SLF56H2Z2L

PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz			TYPICAL PERFORMANCE - NOT GUARANTEED VALUES	
TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	3	338	Start Configuration	DOL
Pull-Up Torque	4.8	159	Starting Current (A)	61.02
Breakdown Torque	8.6	284	No-Load Current (A)	2
Full Load Torque	10.3	100	No-Load Power Factor	-

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	-	-	-	7.8	-	8.9
Efficiency (%)	-	-	-	83.7	-	84.8
Speed (r/min)	-	-	-	3521	-	3504
Power Factor (cosΦ)	-	-	-	1	-	1
Input Power (kW)	-	-	-	-	-	-


Questions? Call 1.888.286.1820



NEMA 10 General Purpose Dual Voltage

DRAWING NUMBER:	NEMA-GP-56-140T
CONNECTION:	-
NUMBER OF LEADS:	6
THERMAL PROTECTION:	Optional

ISSUED DATE	01/08/25
GENERAL PURPOSE SINGLE PHASE MOTORS	



TEFC 56HC

DRAWING NUMBER:	BL1-RS-TF-56HC-RND-01	ISSUED DATE	01/08/25
DIMENSIONS:	Inches		
MOUNTING:	Round Body/C-Flange	GENERAL PURPOSE SINGLE PHASE MOTORS	
CASING MATERIAL:	Rolled Steel		