

NEMA

Model GPS0032BS-TC-01
MFG PN: SLF145T3Z2L-CAN

Model **GPS0032BS-TC-01**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GPS0032BS-TC-01	3	3510	208-230	1	60	145TC	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6




Model GPS0032BS-TC-01
MFG PN: SLF145T3Z2L-CAN

ELECTRICAL DATA		
Rated Motor Output Power	3	HP
	-	kW
Rated Motor Speed	3510	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	208-230	V/60Hz
	-	V/50Hz
Rated Motor Current	13.0/11.7	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	1	Ø
Locked Rotor Current @ High Voltage	92.54	A (I _n) @ 60Hz
FI Current @ 208V	13	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	-	@ 50Hz
KVA Code	J	60Hz
	-	50Hz
Nominal Efficiency	84	% @ 60Hz
Nominal Power Factor	0.98	cosΦ @ 60Hz
Leads (Qty, Size)	4	14
Connection	-	-
Coil Resistance	-	Ω
Start Capacitor	250/300	µF/V
Run Capacitor	40/450	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	-	-
Constant Torque	-	-
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	78.7	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	145TC	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	49 lbs.	
Casing Material / Fan Cover	Rolled Steel	Steel
Shaft Material	1045	
NEMA Design	L	
Degree of Protection (IP)	54	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	NO	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6205 2RS	
Bearing ODE Side	6203 2RS	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820

Model GPS0032BS-TC-01
MFG PN: SLF145T3Z2L-CAN



NAMEPLATE LAYOUT



TECHTOP

Date of Mfg:

SER No.

GEN. PURPOSE SINGLE PHASE MOTOR

MODEL:

MFG PN:SLF

FRAME: HP: RPM: SF:

VOLTS: HZ: AMPS:

KVA Code: PF: EFF: DUTY: CONT

DES: INS.CLASS: AMBIENT: 40 °C

ENCL: CAP: µF V

DE. BRG: ZZ ODE. BRG: ZZ

WIRING DIAGRAM



C US
224693



*For max speed please contact Techtop Canada

Questions? Call 1.888.286.1820

NEMA

Model GPS0032BS-TC-01
MFG PN: SLF145T3Z2L-CAN




PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz			TYPICAL PERFORMANCE - NOT GUARANTEED VALUES	
TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	4.5	279	Start Configuration	DOL
Pull-Up Torque	9.5	211	Starting Current (A)	92.54
Breakdown Torque	11.4	253	No-Load Current (A)	2.2
Full Load Torque	12.5	100	No-Load Power Factor	-

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	-	-	-	11.7	-	13.5
Efficiency (%)	-	-	-	82.4	-	82.1
Speed (r/min)	-	-	-	3504	-	3479
Power Factor (cosΦ)	-	-	-	1	-	-
Input Power (kW)	-	-	-	2.67	-	-

Questions? Call 1.888.286.1820




Model **GPS0032BS-TC-01**
MFG PN: SLF145T3Z2L-CAN



NEMA 1Ø General Purpose Single

DRAWING NUMBER:	NEMA-GP-180T-210T
CONNECTION:	-
NUMBER OF LEADS:	4
THERMAL PROTECTION:	Optional

ISSUED DATE	01/08/25
GENERAL PURPOSE SINGLE PHASE MOTORS	



DRAWING NUMBER:	BL1-RS-TF-140TC-01	ISSUED DATE	01/08/25
DIMENSIONS:	Inches		
MOUNTING:	Rigid/C-Flange	GENERAL PURPOSE SINGLE PHASE MOTORS	
CASING MATERIAL:	Rolled Steel		