

NEMA

Model JPA0022DP
MFG PN: T145T 2U2B

Model JPA0022DP

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
JPA0022DP	2	3500	230/460	3	60	145JP	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model JPA0022DP
MFG PN: T145T 2U2B


ELECTRICAL DATA		
Rated Motor Output Power	2	HP
	-	kW
Rated Motor Speed	3500	r/min 60Hz
	2880	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	5.18/2.59	A (I _n) @ 60Hz
	6.16/3.08	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	23.6	A (I _n) @ 60Hz
FI Current @ 208V	5.58	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	L	60Hz
	H	50Hz
Nominal Efficiency	85.5	% @ 60Hz
Nominal Power Factor	0.85	cosΦ @ 60Hz
Leads (Qty, Size)	9	18
Connection	YY/Y	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	1000:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	47	°C @ 60Hz
	68	°C @ 50Hz

GENERAL DATA		
Frame Size	145JP	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	29.5 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	304 SS	
NEMA Design	B	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6206 2RS	
Bearing ODE Side	6205 2RS	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	77.2	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T2D	-

Questions? Call 1.888.286.1820

NEMA

Model JPA0022DP
MFG PN: T145T 2U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	2	2
RPM	3500	2880
Voltage	230/460	190/380
Full Load Amps	5.18/2.59	6.16/3.08
Service Factor	1.25	1
KVA Code	L	H
Full Load Amps (208V)	5.58	-
Nominal Efficiency	85.5	83.8
Nominal Power Factor	0.85	-
Design	B	
Frame	145JP	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6206 2RS	
Opposite Drive End Bearing	6205 2RS	
Weight (lbs)	29.5	

NAMEPLATE LAYOUT

TECHTOP INDUSTRIAL THREE PHASE PUMP MOTOR
INVERTER DUTY 1000:1 VT - 1.0 SF

MODEL MFG PN

60Hz 50Hz MFG DATE

HP RPM SER #

VOLT DESIGN

FLA FRAME

SF ENCL / IP

KVA CODE DUTY

NOM.EFF INS CL

EFF 75% AMB

PF DE

USABLE AT 208V ODE

NEMA Premium WEIGHT lbs

TECHTOPCANADA.COM

CLASS 1, DIV 2, GROUPS A, B, C AND D

MADE IN CHINA

CC088A
E323353
SP
224653
Energy Verified Only

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	1000:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Division II
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model JPA0022DP
MFG PN: T145T 2U2B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	3	283	Start Configuration	DOL
Pull-Up Torque	5.3	178	Starting Current (A)	23.6
Breakdown Torque	10.9	362	No-Load Current (A)	1.3
Full Load Torque	8.5	100	No-Load Power Factor	0.12



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	1.4	1.7	2.1	2.6	3.1	3.1
Efficiency (%)	74.8	83.3	85.7	86	85.3	85.3
Speed (r/min)	3575	3556	3534	3509	3482	3482
Power Factor (cosΦ)	0.46	0.67	0.79	0.85	0.88	0.88
Input Power (kW)	0.5	0.9	1.31	1.75	2.2	2.2


Questions? Call 1.888.286.1820



Model JPA0022DP
MFG PN: T145T 2U2B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y	ISSUED DATE	14/08/25
CONNECTION:	YY/Y	PREMIUM JM-JP PUMP MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



NEMA Premium TEFC 145JP

DRAWING NUMBER:

GR3-AL-TF-140JP

DIMENSIONS:

Inches

MOUNTING:

Rigid/C-Flange

CASING MATERIAL:

Cast Aluminum

ISSUED DATE

14/08/25

PREMIUM JM-JP PUMP MOTORS