

NEMA

Model JPA0074DP
MFG PN: T213T 7.5U4B

Model JPA0074DP

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
JPA0074DP	7.5	1765	230/460	3	60	213JP	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model JPA0074DP
MFG PN: T213T 7.5U4B


ELECTRICAL DATA		
Rated Motor Output Power	7.5	HP
	-	kW
Rated Motor Speed	1765	r/min 60Hz
	1460	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	17.7/8.86	A (I _n) @ 60Hz
	20.8/10.4	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	88.9	A (I _n) @ 60Hz
FI Current @ 208V	19.2	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	L	60Hz
	J	50Hz
Nominal Efficiency	91.7	% @ 60Hz
Nominal Power Factor	0.85	cosΦ @ 60Hz
Leads (Qty, Size)	9	14
Connection	YY/Y	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	1000:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	38	°C @ 60Hz
	52	°C @ 50Hz

GENERAL DATA		
Frame Size	213JP	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	113 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	304 SS	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6210 2RS	
Bearing ODE Side	6208 2RS	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	70.8	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model JPA0074DP
MFG PN: T213T 7.5U4B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	7.5	7.5
RPM	1765	1460
Voltage	230/460	190/380
Full Load Amps	17.7/8.86	20.8/10.4
Service Factor	1.25	1
KVA Code	L	J
Full Load Amps (208V)	19.2	-
Nominal Efficiency	91.7	90.4
Nominal Power Factor	0.85	-
Design	A	
Frame	213JP	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6210 2RS	
Opposite Drive End Bearing	6208 2RS	
Weight (lbs)	113	

NAMEPLATE LAYOUT

TECHTOP		INDUSTRIAL THREE PHASE PUMP MOTOR INVERTER DUTY 1000:1 VT - 1.0 SF	
MODEL		MFG PN	
60Hz		50Hz	
HP		MFG DATE	
RPM		SER #	
VOLT		DESIGN	
FLA		FRAME	
SF		ENCL / IP	
KVA CODE		DUTY	
NOM.EFF		INS CL	
EFF 75%		AMB	
PF		DE	
USABLE AT 208V		ODE	
NEMA Premium® TECHTOPCANADA.COM		WEIGHT	lbs
CLASS 1, DIV 2, GROUPS A, B, C AND D		MADE IN CHINA	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	1000:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Division II
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model JPA0074DP
MFG PN: T213T 7.5U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	22.3	264	Start Configuration	DOL
Pull-Up Torque	42	188	Starting Current (A)	88.9
Breakdown Torque	85.5	383	No-Load Current (A)	4
Full Load Torque	58.9	100	No-Load Power Factor	0.07



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	4.4	5.6	7.2	9	11	11
Efficiency (%)	84.7	90.1	91.3	91.3	90.7	90.7
Speed (r/min)	1793	1786	1778	1770	1761	1761
Power Factor (cosΦ)	0.46	0.68	0.79	0.84	0.87	0.87
Input Power (kW)	1.62	3.05	4.52	6.02	7.58	7.58


Questions? Call **1.888.286.1820**



Model JPA0074DP
MFG PN: T213T 7.5U4B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y	ISSUED DATE	25/08/25
CONNECTION:	YY/Y	PREMIUM JM-JP PUMP MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



 TECHTOP <i>You can't top a Techtop.</i>		NEMA Premium TEFC 213JP	
DRAWING NUMBER:	GR3-AL-TF-210JP	ISSUED DATE	25/08/25
DIMENSIONS:	Inches	PREMIUM JM-JP PUMP MOTORS	
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Cast Aluminum		