

NEMA

Model JPC0156DP
MFG PN: T284T15U6B

Model JPC0156DP

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
JPC0156DP	15	1180	230/460	3	60	284JP	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model JPC0156DP
MFG PN: T284T15U6B


ELECTRICAL DATA		
Rated Motor Output Power	15	HP
	-	kW
Rated Motor Speed	1180	r/min 60Hz
	970	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	37.8/18.9	A (I _n) @ 60Hz
	45/22.5	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	156.9	A (I _n) @ 60Hz
FI Current @ 208V	41.82	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	L	60Hz
	H	50Hz
Nominal Efficiency	91.7	% @ 60Hz
Nominal Power Factor	0.81	cosΦ @ 60Hz
Leads (Qty, Size)	12	12
Connection	DD/D	-
Coil Resistance	30	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	1000:1	0.06 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	41.9	°C @ 60Hz
	57.2	°C @ 50Hz

GENERAL DATA		
Frame Size	284JP	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	392.9 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	304 SS	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	NO
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6311 C3	
Bearing ODE Side	6311 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	5.73	
Sound Pressure @ 3 FT dBA	71.2	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model JPC0156DP
MFG PN: T284T15U6B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	15	15
RPM	1180	970
Voltage	230/460	190/380
Full Load Amps	37.8/18.9	45/22.5
Service Factor	1.25	1
KVA Code	L	H
Full Load Amps (208V)	41.82	-
Nominal Efficiency	91.7	89.8
Nominal Power Factor	0.81	-
Design	A	
Frame	284JP	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6311 C3	
Opposite Drive End Bearing	6311 C3	
Weight (lbs)	392.9	

NAMEPLATE LAYOUT

TECHTOP		INDUSTRIAL THREE PHASE PUMP MOTOR INVERTER DUTY 1000:1 VT - 1.0 SF	
MODEL		TECHTOPCANADA.COM	
NEMA Premium		60Hz	50Hz
HP		MFG PN	
RPM		MFG DATE	
VOLT		SER #	
FLA		DESIGN	
SF		FRAME	
KVA CODE		ENCL	
NOM.EFF		IP	
USABLE AT 208V 60Hz		DUTY	
FLA		INS CL	
		AMB	
		WEIGHT	
		lbs	
BEARING SIZE		IEEE 45 MARINE DUTY	
DE	ODE		
GREASE: MOBIL POLYREX EM			
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D			

VFD DUTY (S.F. 1.0)

Variable Torque
Constant Torque

RATIO

1000:1
15:1

Hz*

0.06 - 60
4 - 60

*For max speed please contact Techtop Canada

HAZARDOUS LOCATIONS

Class / Division
Groups

CSA CERTIFIED


Class I, Div. 2
A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model JPC0156DP
MFG PN: T284T15U6B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	199	298	Start Configuration	DOL
Pull-Up Torque	135.5	203	Starting Current (A)	156.9
Breakdown Torque	231	346	No-Load Current (A)	11.4
Full Load Torque	66.8	100	No-Load Power Factor	-


TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	12.2	14.1	16.8	20.1	23.9	23.9
Efficiency (%)	84.1	89.9	91.3	91.4	91	91
Speed (r/min)	1197	1193	1190	1186	1182	1182
Power Factor (cosΦ)	0.34	0.54	0.67	0.75	0.79	0.79
Input Power (kW)	3.27	6.12	9.04	12.03	15.12	15.12

Questions? Call 1.888.286.1820



Model JPC0156DP
MFG PN: T284T15U6B



HIGH VOLTAGE
(Δ)




LOW VOLTAGE
(ΔΔ)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø DD/D 12-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-12-DD-D	ISSUED DATE	08/09/25
CONNECTION:	DD/D	PREMIUM JM-JP PUMP MOTORS	
NUMBER OF LEADS:	12		
THERMAL PROTECTION:	-		



NEMA Premium TEFC 284JP

DRAWING NUMBER:	GR3-CI-TF-284JP-CFC	ISSUED DATE	08/09/25
DIMENSIONS:	Inches		
MOUNTING:	Rigid/C-Flange	PREMIUM JM-JP PUMP MOTORS	
CASING MATERIAL:	Cast Iron		