

NEMA

Model JPC0206DP
MFG PN: T286T 20U6B

Model JPC0206DP

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
JPC0206DP	20	1180	230/460	3	60	286JP	Rigid/C-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton

PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg


PHONE 204.633.2779
EMAIL infoWEST@techtopcanada.com

Calgary

PHONE 403.313.6363
EMAIL infoWEST@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoWEST@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA


Model JPC0206DP
MFG PN: T286T 20U6B

ELECTRICAL DATA		
Rated Motor Output Power	20	HP
	-	kW
Rated Motor Speed	1180	r/min 60Hz
	970	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	49.8/24.9	A (I _n) @ 60Hz
	60/30	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	218.5	A (I _n) @ 60Hz
FI Current @ 208V	55.08	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	K	60Hz
	H	50Hz
Nominal Efficiency	91.7	% @ 60Hz
Nominal Power Factor	0.82	cosΦ @ 60Hz
Leads (Qty, Size)	12	12
Connection	DD/D	-
Coil Resistance	26.8	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	1000:1	0.06 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	59.7	°C @ 60Hz
	83.8	°C @ 50Hz

GENERAL DATA		
Frame Size	286JP	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	432.6 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	304 SS	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6311 C3	
Bearing ODE Side	6311 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	6.64	
Sound Pressure @ 3 FT dBA	71.2	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

Model JPC0206DP
MFG PN: T286T 20U6B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	20	20
RPM	1180	970
Voltage	230/460	190/380
Full Load Amps	49.8/24.9	60/30
Service Factor	1.25	1
KVA Code	K	H
Full Load Amps (208V)	55.08	-
Nominal Efficiency	91.7	89.2
Nominal Power Factor	0.82	-
Design	A	
Frame	286JP	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6311 C3	
Opposite Drive End Bearing	6311 C3	
Weight (lbs)	432.6	

NAMEPLATE LAYOUT

		INDUSTRIAL THREE PHASE PUMP MOTOR INVERTER DUTY 1000:1 VT - 1.0 SF	
MODEL			TECHTOPCANADA.COM
	60Hz	50Hz	MFG PN
			MFG DATE
	HP		SER #
	RPM		DESIGN
	VOLT		FRAME
	FLA		ENCL
	SF		IP
	KVA CODE		DUTY
NOM.EFF		INS CL	AMB
WEIGHT		lbs	

USABLE AT 208V 60Hz	
FLA	

BEARING SIZE	
DE	ODE
GREASE: MOBIL POLYREX EM	

MADE IN CHINA

CLASS 1, DIV 2, GROUPS A, B, C AND D

IEEE 55 MARINE DUTY

Energy Verifier
Only

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	1000:1	0.06 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820



Model **JPC0206DP**
MFG PN: T286T 20U6B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)
Locked Rotor Torque	271.5	305
Pull-Up Torque	188.7	212
Breakdown Torque	292	328
Full Load Torque	89	100

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

PERFORMANCE VALUES	
Start Configuration	DOL
Starting Current (A)	218.5
No-Load Current (A)	14.9
No-Load Power Factor	-

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	16.0	18.7	22.3	26.9	32.1	32.1
Efficiency (%)	85.2	90.7	92.0	92.1	91.7	91.7
Speed (r/min)	1197.0	1193.0	1190.0	1186.0	1182.0	1182.0
Power Factor (cosΦ)	0.35	0.56	0.69	0.76	0.80	0.80
Input Power (kW)	4.4	8.3	12.2	16.3	20.4	20.4

Questions? Call 1.888.286.1820



HIGH VOLTAGE
(Δ)



LOW VOLTAGE
(ΔΔ)



- NOTES:
1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 5. DIAGRAMS FOR REFERENCE ONLY



DRAWING NUMBER:	NEMA-3-12-DD-D
CONNECTION:	DD/D
NUMBER OF LEADS:	12
THERMAL PROTECTION:	-

NEMA 3Ø DD/D 12-Lead Dual Voltage

ISSUED DATE	29/10/25
PREMIUM JM-JP PUMP MOTORS	



NEMA Premium TEFC 286JP

DRAWING NUMBER:	GR3-CI-TF-286JP-CFC	ISSUED DATE	29/10/25
DIMENSIONS:	Inches	PREMIUM JM-JP PUMP MOTORS	
MOUNTING:	Rigid/C-Flange		
CASING MATERIAL:	Cast Iron		