

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12739547
Catalog # : CT000402NPW22

Frame	: 143/5TC	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.94/1.47 A	Protection degree	: IP55
L. R. Amperes	: 24.1/12.1 A	Cooling method	: IC411 - TEFC
LRC	: 8.2x(Code L)	Mounting	: F-1
No load current	: 1.54/0.770 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3500 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 1.50 ft.lb	Approx. weight ³	: 36.4 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 310 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0332 sq.ft.lb		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	75.0	79.0	80.0	Max. traction	: 21 lb
Power Factor	0.63	0.74	0.80	Max. compression	: 64 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
22.8	16.9	16.0	14.5	8.4	6.7	4.4

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6205 ZZ	: 6204 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: 00088	

Notes
USABLE @208V 3.16A SF 1.15 SFA 3.64A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	03/07/2026			
			Page	Revision
			1 / 6	

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12739547

Catalog # : CT000402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 2.94/1.47 A
LRC : 8.2
Rated torque : 1.50 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 310 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0332 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6Revision		
Checked by				
Date	03/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12739547

Catalog # : CT000402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 2.94/1.47 A
LRC : 8.2
Rated torque : 1.50 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 310 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0332 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	03/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12739547

Catalog # : CT000402NPW22

Performance : 230/460 V 60 Hz 2P

Rated current : 2.94/1.47 A
LRC : 8.2
Rated torque : 1.50 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 310 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0332 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K

Heating constant

Cooling constant

Rev.

Changes Summary

Performed

Checked

Date

Performed by

Checked by

Date

03/07/2026

Page

4 / 6


Revision

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	03/07/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12739547

Catalog # : CT000402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 2.94/1.47 A
LRC : 8.2
Rated torque : 1.50 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 310 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0332 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					

