

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12447060
Catalog # : CT015402NPW22

Frame	: 254/6TC	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 34.5/17.2 A	Protection degree	: IP55
L. R. Amperes	: 231/116 A	Cooling method	: IC411 - TEFC
LRC	: 6.7x(Code G)	Mounting	: F-1
No load current	: 10.0/5.00 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3535 rpm	Noise level ²	: 72.0 dB(A)
Slip	: 1.81 %	Starting method	: Direct On Line
Rated torque	: 22.3 ft.lb	Approx. weight ³	: 236 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 1.26 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	89.5	91.0	91.0	Max. traction	: 174 lb
Power Factor	0.00	0.77	0.85	0.88	Max. compression	: 445 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.5	6.3	5.9	5.2	3.0	2.2	1.4

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 C3	6209 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	19000 h	20000 h
Lubricant amount	:	13 g	9 g
Lubricant type	:	Mobil Polyrex EM	

Notes

USABLE @208V 38.0A SF 1.15 SFA 43.7A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 6		
Checked by				
Date	10/07/2026			

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060

Catalog # : CT015402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 34.5/17.2 A
LRC : 6.7
Rated torque : 22.3 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3535 rpm

Moment of inertia (J) : 1.26 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	10/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060

Catalog # : CT015402NPW22



Performance : 230/460 V 60 Hz 2P

Rated current : 34.5/17.2 A
LRC : 6.7
Rated torque : 22.3 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3535 rpm

Moment of inertia (J) : 1.26 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 3 / 6		Revision
Checked by					
Date					

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060

Catalog # : CT015402NPW22

Performance : 230/460 V 60 Hz 2P

Rated current : 34.5/17.2 A
LRC : 6.7
Rated torque : 22.3 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3535 rpm

Moment of inertia (J) : 1.26 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 4 / 6		Revision
Checked by					
Date	10/07/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				5 / 6	
Date	10/07/2026				

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060

Catalog # : CT015402NPW22





Performance : 230/460 V 60 Hz 2P

Rated current : 34.5/17.2 A
LRC : 6.7
Rated torque : 22.3 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3535 rpm

Moment of inertia (J) : 1.26 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 6 / 6
Checked by				
Date				
	10/07/2026			Revision



15 HP 02 Poles 60 Hz										A
						Scale 1 : 8				
						HYBRISUSER				00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER	 THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 254/6TC IP55 TEFC				PREVIEW WDD 00				
CHECKED										
RELEASED										
REL. DATE										
						SHEET		1 / 1		