

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase
Product code : 13025624
Catalog # : CT020408NPW22

Frame	: 324/6TC	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 20 HP (15 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 59.6/29.8 A	Protection degree	: IP55
L. R. Amperes	: 298/149 A	Cooling method	: IC411 - TEFC
LRC	: 5.0x(Code G)	Mounting	: F-1
No load current	: 34.0/17.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 881 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.11 %	Starting method	: Direct On Line
Rated torque	: 119 ft.lb	Approx. weight ³	: 452 lb
Locked rotor torque	: 190 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 9.37 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	89.5	90.2	90.2	Max. traction	: 897 lb
Power Factor	0.50	0.63	0.70	Max. compression	: 1422 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
10.5	8.9	8.6	5.8	4.2	3.2	2.4

	Drive end	Non drive end
Bearing type	: 6312 C3	: 6212 C3
Sealing	: V'Ring	: V'Ring
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 21 g	: 13 g
Lubricant type	: Mobil Polyrex EM	

Notes

USABLE @208V 62.6A SF 1.15 SFA 72.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	13/07/2026			

Page 1 / 6
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13025624

Catalog # : CT020408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 59.6/29.8 A
LRC : 5.0
Rated torque : 119 ft.lb
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 881 rpm

Moment of inertia (J) : 9.37 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	13/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13025624

Catalog # : CT020408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 59.6/29.8 A
LRC : 5.0
Rated torque : 119 ft.lb
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 881 rpm

Moment of inertia (J) : 9.37 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	13/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13025624

Catalog # : CT020408NPW22

Performance : 230/460 V 60 Hz 8P

Rated current : 59.6/29.8 A
LRC : 5.0
Rated torque : 119 ft.lb
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 881 rpm

Moment of inertia (J) : 9.37 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant

Rev.

Changes Summary

Performed

Checked

Date

Performed by

Checked by

Date

13/07/2026

Page

4 / 6


Revision

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					Page 5 / 6
Checked by					
Date	13/07/2026				
					Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 13025624

Catalog # : CT020408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 59.6/29.8 A
LRC : 5.0
Rated torque : 119 ft.lb
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 881 rpm

Moment of inertia (J) : 9.37 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 6	Revision
Checked by					
Date	13/07/2026				

