

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12717834
Catalog # : HT010508NPW22

Frame	: 284/6T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 11.2 A	Protection degree	: IP55
L. R. Amperes	: 63.9 A	Cooling method	: IC411 - TEFC
LRC	: 5.7x(Code H)	Mounting	: F-1
No load current	: 5.68 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 882 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 2.00 %	Starting method	: Direct On Line
Rated torque	: 59.5 ft.lb	Approx. weight ³	: 373 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 7.20 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	88.1	89.5	89.5	Max. traction	: 446 lb
Power Factor	0.52	0.65	0.75	Max. compression	: 800 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.4	9.6	8.8	6.0	4.2	3.0	2.2

	Drive end	Non drive end
Bearing type	: 6311 C3	: 6211 C3
Sealing	: V'Ring	: V'Ring
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 18 g	: 11 g
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 6		
Checked by				
Date	28/07/2026			

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717834

Catalog # : HT010508NPW22



Performance : 575 V 60 Hz 8P

Rated current	: 11.2 A	Moment of inertia (J)	: 7.20 sq.ft.lb
LRC	: 5.7	Duty cycle	: Cont.(S1)
Rated torque	: 59.5 ft.lb	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.25
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 882 rpm	Design	: B

Locked rotor time : 36s (cold) 20s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	28/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717834

Catalog # : HT010508NPW22



Performance : 575 V 60 Hz 8P

Rated current : 11.2 A
LRC : 5.7
Rated torque : 59.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 240 %
Rated speed : 882 rpm

Moment of inertia (J) : 7.20 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	28/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717834

Catalog # : HT010508NPW22

Performance : 575 V 60 Hz 8P

Rated current	: 11.2 A	Moment of inertia (J)	: 7.20 sq.ft.lb
LRC	: 5.7	Duty cycle	: Cont.(S1)
Rated torque	: 59.5 ft.lb	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.25
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 882 rpm	Design	: B

Heating constant

Cooling constant

Rev.

Changes Summary

Performed

Checked

Date

Performed by

Checked by

Date

28/07/2026

Page

4 / 6


Revision

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	28/07/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717834

Catalog # : HT010508NPW22



Performance : 575 V 60 Hz 8P

Rated current : 11.2 A
LRC : 5.7
Rated torque : 59.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 240 %
Rated speed : 882 rpm

Moment of inertia (J) : 7.20 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 6Revision			
Checked by					
Date	28/07/2026				

