

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11568843
Catalog # : HT015408NPW22

Frame	: 284/6T	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 40.1/20.0 A	Protection degree	: IP55
L. R. Amperes	: 220/110 A	Cooling method	: IC411 - TEFC
LRC	: 5.5x(Code G)	Mounting	: F-1
No load current	: 20.0/10.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 880 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 89.5 ft.lb	Approx. weight ³	: 417 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 8.18 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	85.5	90.0	89.5	Max. traction	: 852 lb
Power Factor	0.61	0.71	0.77	Max. compression	: 1233 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.4	9.9	9.3	5.6	4.1	2.8	2.1

	Drive end	Non drive end
Bearing type	: 6311 C3	: 6211 C3
Sealing	: V'Ring	: V'Ring
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 18 g	: 11 g
Lubricant type	: Mobil Polyrex EM	

Notes

USABLE @208V 42.9A SF 1.15 SFA 49.3A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/07/2026			
		Page		Revision
		1 / 6		

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568843

Catalog # : HT015408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 40.1/20.0 A
LRC : 5.5
Rated torque : 89.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 229 %
Rated speed : 880 rpm

Moment of inertia (J) : 8.18 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 39s (cold) 22s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6 Revision		
Checked by				
Date	28/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568843

Catalog # : HT015408NPW22



Performance : 230/460 V 60 Hz 8P

Rated current : 40.1/20.0 A
LRC : 5.5
Rated torque : 89.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 229 %
Rated speed : 880 rpm

Moment of inertia (J) : 8.18 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	28/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568843

Catalog # : HT015408NPW22

Performance : 230/460 V 60 Hz 8P

Rated current : 40.1/20.0 A
LRC : 5.5
Rated torque : 89.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 229 %
Rated speed : 880 rpm

Moment of inertia (J) : 8.18 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	28/07/2026			4 / 6	

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					Page 5 / 6
Checked by					
Date	28/07/2026				
					Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568843

Catalog # : HT015408NPW22





Performance : 230/460 V 60 Hz 8P

Rated current : 40.1/20.0 A
LRC : 5.5
Rated torque : 89.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 229 %
Rated speed : 880 rpm

Moment of inertia (J) : 8.18 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					



Color RAL 5009
Painting plan 203A
Mounting NEMA F-1
Mounting B3R(D)

15 HP 08 Poles 60 Hz										A
						Scale 1 : 9				
						HYBRISUSER				00
ECM		LOC		SUMMARY OF MODIFICATIONS		EXECUTED		CHECKED		RELEASED
										DATE
										VER
EXECUTED		HYBRISUSER		 THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 284/6T IP55 TEFC		PREVIEW WDD 00				
CHECKED										
RELEASED										
REL. DATE										
						SHEET		1 / 1		