

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase
Product code : 11165470
Catalog # : HT040406NPW22

Frame	: 364/5T	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 93.0/46.5 A	Protection degree	: IP55
L. R. Amperes	: 595/298 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code G)	Mounting	: F-1
No load current	: 33.0/16.5 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1183 rpm	Noise level ²	: 66.0 dB(A)
Slip	: 1.42 %	Starting method	: Direct On Line
Rated torque	: 178 ft.lb	Approx. weight ³	: 833 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 21.8 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	93.6	93.6	94.1	Max. traction	: 1254 lb
Power Factor	0.73	0.82	0.86	Max. compression	: 2114 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.1	5.0	4.4	2.8	1.9	1.1	0.8

	Drive end	Non drive end
Bearing type	: 6314 C3	: 6314 C3
Sealing	: WSeal	: WSeal
Lubrication interval	: 17000 h	: 17000 h
Lubricant amount	: 27 g	: 27 g
Lubricant type	: Mobil Polyrex EM	

Notes

USABLE @208V 103A SF 1.10 SFA 113A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	30/07/2026			

Page 1 / 6
Revision

TORQUE AND CURRENT VS SPEED CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165470

Catalog # : HT040406NPW22



Performance : 230/460 V 60 Hz 6P

Rated current : 93.0/46.5 A
LRC : 6.4
Rated torque : 178 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 1183 rpm

Moment of inertia (J) : 21.8 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Locked rotor time : 37s (cold) 21s (hot)

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 6Revision		
Checked by				
Date	30/07/2026			

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165470

Catalog # : HT040406NPW22



Performance : 230/460 V 60 Hz 6P

Rated current : 93.0/46.5 A
LRC : 6.4
Rated torque : 178 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 1183 rpm

Moment of inertia (J) : 21.8 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	30/07/2026			

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165470

Catalog # : HT040406NPW22

Performance : 230/460 V 60 Hz 6P

Rated current : 93.0/46.5 A
LRC : 6.4
Rated torque : 178 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 1183 rpm

Moment of inertia (J) : 21.8 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Heating constant

Cooling constant


Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 4 / 6		Revision
Checked by					
Date	30/07/2026				

THERMAL LIMIT CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____



Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	30/07/2026				
				Page 5 / 6	Revision

VFD OPERATION CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11165470

Catalog # : HT040406NPW22





Performance : 230/460 V 60 Hz 6P


Rated current : 93.0/46.5 A
LRC : 6.4
Rated torque : 178 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 1183 rpm

Moment of inertia (J) : 21.8 sq.ft.lb
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 6	
Date					



Without vertical jackscrews
Color RAL 5009
Painting plan 203A
Mounting B3R(D)



40 HP 06 Poles 60 Hz										A
						Scale 1 : 11				
				HYBRISUSER						00
ECM		LOC		SUMMARY OF MODIFICATIONS		EXECUTED		CHECKED		RELEASED
EXECUTED		HYBRISUSER		 THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 364/5T IP55 TEFC		PREVIEW WDD 00				
CHECKED										
RELEASED										
REL. DATE										
						SHEET		1 / 1		