



Model MSPH71A4C
MFG PN: EMU714D0301

Model **MSPH71A4C**

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
MSPH71A4C	0.33	1610	115/230	1	60	71	B3	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techttopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techttopcanada.com

Moncton

PHONE 506.386.5794
EMAIL infoNB@techttopcanada.com

Winnipeg


PHONE 204.633.2779
EMAIL infoWEST@techttopcanada.com

Calgary

PHONE 403.313.6363
EMAIL infoWEST@techttopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoWEST@techttopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6



Model MSPH71A4C
MFG PN: EMU714D0301

ELECTRICAL DATA		
Rated Motor Output Power	0.33	HP
	0.25	kW
Rated Motor Speed	1610	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	115/230	V/60Hz
	-	V/50Hz
Rated Motor Current	4/2.1	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	1	Ø
Locked Rotor Current @ High Voltage	-	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1	@ 60Hz
	-	@ 50Hz
KVA Code	-	60Hz
	-	50Hz
Nominal Efficiency	60.9	% @ 60Hz
Nominal Power Factor	0.85	cosΦ @ 60Hz
Leads (Qty, Size)	-	-
Connection	-	-
Coil Resistance	-	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	-	-
Constant Torque	-	-
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	-	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	71	
Enclosure	TEFC	
Mounting	B3	
Approximate Weight (lbs.)	12.7 lbs.	
Casing Material / Fan Cover	Cast Aluminum	Steel
Shaft Material	1045	
NEMA Design	-	
Degree of Protection (IP)	54	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	NO	
Duty	Cont. / S1	
Conduit Box Location	F0	
Feet Removable / Double Drilled	YES	NO
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6202 2RS CM	
Bearing ODE Side	6202 2RS CM	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	DE	
Moment of Inertia (lb-ft²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-


Questions? Call 1.888.286.1820



Model MSPH71A4C
MFG PN: EMU714D0301

NAMEPLATE DATA	60Hz	50Hz
Horse Power	0.33/0.25	0.33/0.25
RPM	1610	-
Voltage	115/230	-
Full Load Amps	4/2.1	-
Service Factor	1	-
KVA Code	-	-
Full Load Amps (208V)	-	-
Nominal Efficiency	60.9	-
Nominal Power Factor	0.85	-
Design	-	
Frame	71	
Enclosure Type	TEFC	
IP Rating	54	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6202 2RS CM	
Opposite Drive End Bearing	6202 2RS CM	
Weight (lbs)	12.7	

NAMEPLATE LAYOUT



CAPACITOR DATA	µF	VOLTAGE
Start Capacitor	-	-
Run Capacitor	-	-

*For max speed please contact Techtop Canada

HAZARDOUS LOCATIONS	-
Class / Division	-
Groups	-

Questions? Call 1.888.286.1820



Model MSPH71A4C
MFG PN: EMU714D0301

PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz			TYPICAL PERFORMANCE - NOT GUARANTEED VALUES	
TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	-	-	Start Configuration	DOL
Pull-Up Torque	-	-	Starting Current (A)	-
Breakdown Torque	-	-	No-Load Current (A)	-
Full Load Torque	1.1	-	No-Load Power Factor	-

% OF RATED LOAD	25	50	75	100	125	S.F. 1
Line Amperes (A)	-	-	-	-	-	-
Efficiency (%)	-	-	-	-	-	-
Speed (r/min)	-	-	-	-	-	-
Power Factor (cosΦ)	-	-	-	-	-	-
Input Power (kW)	-	-	-	-	-	-

Questions? Call 1.888.286.1820



Model MSPH71A4C
MFG PN: EMU714D0301



DRAWING NUMBER:	-	ISSUED DATE	19/08/26
CONNECTION:	-	METRIC SINGLE PHASE MOTORS	
NUMBER OF LEADS:	-		
THERMAL PROTECTION:	-		



Model **MSPH71A4C**
MFG PN: EMU714D0301



TEFC 71

DRAWING NUMBER:	-	ISSUED DATE	19/08/26
DIMENSIONS:	mm		
MOUNTING:	B3	METRIC SINGLE PHASE MOTORS	
CASING MATERIAL:	Cast Aluminum		