

NEMA

Model GRC0014D-TD
MFG PN: T145T1.5U4B

Model GRC0014D-TD

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC0014D-TD	1.5	1740	230/460	3	60	145TD	Rigid/D-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC0014D-TD
MFG PN: T145T1.5U4B

ELECTRICAL DATA		
Rated Motor Output Power	1.5	HP
	-	kW
Rated Motor Speed	1740	r/min 60Hz
	1410	r/min 50Hz
Rated Motor Voltage (+/-10%)	230/460	V/60Hz
	190/380	V/50Hz
Rated Motor Current	4.4/2.2	A (I _n) @ 60Hz
	5/2.5	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	16.74	A (I _n) @ 60Hz
FI Current @ 208V	4.79	A (I _n) @ 60Hz
Service Factor	1.25	@ 60Hz
	1	@ 50Hz
KVA Code	L	60Hz
	H	50Hz
Nominal Efficiency	86.5	% @ 60Hz
Nominal Power Factor	0.75	cosΦ @ 60Hz
Leads (Qty, Size)	9	2
Connection	YY/Y	-
Coil Resistance	9.069	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	36.8	°C @ 60Hz
	51	°C @ 50Hz

GENERAL DATA		
Frame Size	145TD	
Enclosure	TEFC	
Mounting	Rigid/D-Flange	
Approximate Weight (lbs.)	58 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	-	
NEMA Design	B	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	YES	NO
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6205 ZZ	
Bearing ODE Side	6205 ZZ	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	0.09	
Sound Pressure @ 3 FT dBA	62.2	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T2D	-



Questions? Call 1.888.286.1820

DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR
PREMIUM T-FRAME CAST IRON MOTORS



NEMA

Model GRC0014D-TD
MFG PN: T145T1.5U4B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	1.5	1.5
RPM	1740	1410
Voltage	230/460	190/380
Full Load Amps	4.4/2.2	5/2.5
Service Factor	1.25	1
KVA Code	L	H
Full Load Amps (208V)	4.79	-
Nominal Efficiency	86.5	83.5
Nominal Power Factor	0.75	-
Design	B	
Frame	145TD	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6205 ZZ	
Opposite Drive End Bearing	6205 ZZ	
Weight (lbs)	58	

NAMEPLATE LAYOUT

		INDUSTRIAL THREE PHASE MOTOR	
		INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF	
MODEL			TECHTOPCANADA.COM
NEMA Premium HP RPM VOLT FLA SF KVA CODE NOM.EFF	60Hz	50Hz	MFG PN
			MFG DATE
			SER #
			DESIGN
			FRAME
			ENCL
			IP
			DUTY
USABLE AT 208V 60Hz	BEARING SIZE		INS CL
FLA	DE	ODE	AMB
GREASE: MOBIL POLYREX EM		WEIGHT	
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC0014D-TD
MFG PN: T145T1.5U4B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	14.1	311	Start Configuration	DOL
Pull-Up Torque	9.8	216	Starting Current (A)	16.74
Breakdown Torque	15.9	351	No-Load Current (A)	1.2
Full Load Torque	4.5	100	No-Load Power Factor	0.08



TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.25
Line Amperes (A)	1.3	1.5	1.8	2.1	2.5	2.5
Efficiency (%)	76.4	84.2	86.1	86	85.1	85.1
Speed (r/min)	1787	1775	1762	1748	1732	1732
Power Factor (cosΦ)	0.36	0.56	0.68	0.76	0.8	0.8
Input Power (kW)	0.36	0.65	0.96	1.28	1.62	1.62


Questions? Call 1.888.286.1820



Model **GRC0014D-TD**
MFG PN: T145T1.5U4B



HIGH VOLTAGE
(Y)




LOW VOLTAGE
(YY)

- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



NEMA 3Ø YY/Y 9-Lead Dual Voltage

DRAWING NUMBER:	NEMA-3-9-YY-Y	ISSUED DATE	11/03/25
CONNECTION:	YY/Y	PREMIUM T-FRAME CAST IRON MOTORS	
NUMBER OF LEADS:	9		
THERMAL PROTECTION:	-		



NEMA Premium TEFC 145TD

DRAWING NUMBER:	GR3-CI-TF-145TD-CFC	ISSUED DATE	11/03/25
DIMENSIONS:	Inches	PREMIUM T-FRAME CAST IRON MOTORS	
MOUNTING:	Rigid/D-Flange		
CASING MATERIAL:	Cast Iron		