

**NEMA**

**Model GRC0026D**  
MFG PN: T184T2U6B

# Model GRC0026D

## Product Data Package



| MODEL    | HP | RPM  | VOLTAGE | PHASE | Hz | FRAME | MOUNT | ENCLOSURE |
|----------|----|------|---------|-------|----|-------|-------|-----------|
| GRC0026D | 2  | 1175 | 230/460 | 3     | 60 | 184T  | Rigid | TEFC      |

### Toronto

**TOLL FREE** 1.888.286.1820  
**PHONE** 905.829.1001  
**EMAIL** info@techtopcanada.com

### Montreal

**TOLL FREE** 1.844.354.5111  
**PHONE** 514.354.1002  
**EMAIL** infoQC@techtopcanada.com

### Moncton


**PHONE** 506.386.5794  
**EMAIL** infoNB@techtopcanada.com

### Winnipeg

**PHONE** 204.633.2779  
**EMAIL** infoMB@techtopcanada.com

### Vancouver

**PHONE** 604.525.1551  
**EMAIL** infoBC@techtopcanada.com



### Index

|                               |     |
|-------------------------------|-----|
| Motor General Data Sheet      | P 2 |
| Nameplate Information         | P 3 |
| Technical Performance Data    | P 4 |
| Motor General Wiring Diagram  | P 5 |
| Motor General Outline Drawing | P 6 |

**NEMA**

**Model GRC0026D**  
**MFG PN: T184T2U6B**

| ELECTRICAL DATA                     |              |                            |
|-------------------------------------|--------------|----------------------------|
| Rated Motor Output Power            | 2            | HP                         |
|                                     | -            | kW                         |
| Rated Motor Speed                   | 1175         | r/min 60Hz                 |
|                                     | 970          | r/min 50Hz                 |
| Rated Motor Voltage (+/-10%)        | 230/460      | V/60Hz                     |
|                                     | 190/380      | V/50Hz                     |
| Rated Motor Current                 | 6.2/3.1      | A (I <sub>n</sub> ) @ 60Hz |
|                                     | 7.2/3.6      | A (I <sub>n</sub> ) @ 50Hz |
| Phase                               | 3            | Ø                          |
| Locked Rotor Current @ High Voltage | 22.65        | A (I <sub>n</sub> ) @ 60Hz |
| FI Current @ 208V                   | 6.89         | A (I <sub>n</sub> ) @ 60Hz |
| Service Factor                      | 1.25         | @ 60Hz                     |
|                                     | 1            | @ 50Hz                     |
| KVA Code                            | L            | 60Hz                       |
|                                     | H            | 50Hz                       |
| Nominal Efficiency                  | 88.5         | % @ 60Hz                   |
| Nominal Power Factor                | 0.68         | cosΦ @ 60Hz                |
| Leads (Qty, Size)                   | 9            | 16                         |
| Connection                          | YY/Y         | -                          |
| Coil Resistance                     | 4.597        | Ω                          |
| Start Capacitor                     | -            | µF/V                       |
| Run Capacitor                       | -            | µF/V                       |
| <b>VFD DUTY (S.F. 1.0)</b>          | <b>RATIO</b> | <b>Hz</b>                  |
| Variable Torque                     | 30:1         | 2 - 60                     |
| Constant Torque                     | 15:1         | 4 - 60                     |
| FULL LOAD TEMPERATURE RISE          |              |                            |
| Full Load Temperature Rise          | 25.9         | °C @ 60Hz                  |
|                                     | 34.2         | °C @ 50Hz                  |

| GENERAL DATA                        |                  |           |
|-------------------------------------|------------------|-----------|
| Frame Size                          | 184T             |           |
| Enclosure                           | TEFC             |           |
| Mounting                            | Rigid            |           |
| Approximate Weight (lbs.)           | 121.4 lbs.       |           |
| Casing Material / Fan Cover         | Cast Iron        | Cast Iron |
| Shaft Material                      | -                |           |
| NEMA Design                         | B                |           |
| Degree of Protection (IP)           | 55               |           |
| Insulation Class / Temp Rise (60Hz) | F                | B         |
| Tropicalization                     | YES              |           |
| Duty                                | Cont. / S1       |           |
| Conduit Box Location                | F1               |           |
| Feet Removable / Double Drilled     | YES              | NO        |
| Paintwork                           | 7024             |           |
|                                     | Graphite Gray    |           |
| MECHANICAL DATA                     |                  |           |
| Bearing DE Side                     | 6306 ZZ          |           |
| Bearing ODE Side                    | 6306 ZZ          |           |
| Grease Type                         | Mobil Polyrex EM |           |
| Compensation Ring (wavy washer)     | NDE              |           |
| Moment of Inertia (lb-ft²)          | 0.53             |           |
| Sound Pressure @ 3 FT dBA           | 59               |           |
| SITE CONDITIONS                     |                  |           |
| Ambient Temperature (°C)            | 40               |           |
| Meters Above Sea Level (MASL)       | 1000             |           |
| HAZARDOUS LOCATIONS                 |                  |           |
| CSA Certified                       | A, B, C & D      |           |
| Temperature Code                    | T3               | -         |


**Questions? Call 1.888.286.1820**

**DATA SHEET: THREE-PHASE SQUIRREL CAGE MOTOR**  
**PREMIUM T-FRAME CAST IRON MOTORS**



**NEMA**

**Model GRC0026D**  
**MFG PN: T184T2U6B**



| NAMEPLATE DATA             | 60Hz       | 50Hz    |
|----------------------------|------------|---------|
| Horse Power                | 2          | 2       |
| RPM                        | 1175       | 970     |
| Voltage                    | 230/460    | 190/380 |
| Full Load Amps             | 6.2/3.1    | 7.2/3.6 |
| Service Factor             | 1.25       | 1       |
| KVA Code                   | L          | H       |
| Full Load Amps (208V)      | 6.89       | -       |
| Nominal Efficiency         | 88.5       | 87.4    |
| Nominal Power Factor       | 0.68       | -       |
| Design                     | B          |         |
| Frame                      | 184T       |         |
| Enclosure Type             | TEFC       |         |
| IP Rating                  | 55         |         |
| Duty                       | Cont. / S1 |         |
| Insulation Class           | F          |         |
| Ambient Rating             | 40         |         |
| Drive End Bearing          | 6306 ZZ    |         |
| Opposite Drive End Bearing | 6306 ZZ    |         |
| Weight (lbs)               | 121.4      |         |

**NAMEPLATE LAYOUT**

|                                                                              |              |                                                                        |                   |
|------------------------------------------------------------------------------|--------------|------------------------------------------------------------------------|-------------------|
| <b>TECHTOP</b>                                                               |              | INDUSTRIAL THREE PHASE MOTOR<br>INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF |                   |
| MODEL                                                                        |              |                                                                        | TECHTOPCANADA.COM |
| <b>NEMA Premium</b><br>HP<br>RPM<br>VOLT<br>FLA<br>SF<br>KVA CODE<br>NOM.EFF | 60Hz         | 50Hz                                                                   | MFG PN            |
|                                                                              |              |                                                                        | MFG DATE          |
|                                                                              |              |                                                                        | SER #             |
|                                                                              |              |                                                                        | DESIGN            |
|                                                                              |              |                                                                        | FRAME             |
|                                                                              |              |                                                                        | ENCL              |
|                                                                              |              |                                                                        | IP                |
|                                                                              |              |                                                                        | DUTY              |
| USABLE AT<br>208V 60Hz                                                       | BEARING SIZE |                                                                        | INS CL            |
| FLA                                                                          | DE           | ODE                                                                    | AMB               |
| GREASE: MOBIL POLYREX EM                                                     |              | WEIGHT                                                                 |                   |
| MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D                           |              | IEEE 45 MARINE DUTY                                                    |                   |

| VFD DUTY (S.F. 1.0) | RATIO | Hz*    |
|---------------------|-------|--------|
| Variable Torque     | 30:1  | 2 - 60 |
| Constant Torque     | 15:1  | 4 - 60 |

\*For max speed please contact Techtop Canada


| HAZARDOUS LOCATIONS | CSA CERTIFIED   |
|---------------------|-----------------|
| Class / Division    | Class I, Div. 2 |
| Groups              | A, B, C & D     |

**Questions? Call 1.888.286.1820**

**NEMA**

**Model GRC0026D**  
MFG PN: T184T2U6B

**Torque Speed (T-n) Curve**






**PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz**

| TORQUE VALUES       | TORQUE (lb-ft) | TORQUE (% FULL LOAD) | PERFORMANCE VALUES   |       |
|---------------------|----------------|----------------------|----------------------|-------|
| Locked Rotor Torque | 24.1           | 270                  | Start Configuration  | DOL   |
| Pull-Up Torque      | 18.5           | 207                  | Starting Current (A) | 22.65 |
| Breakdown Torque    | 30.9           | 346                  | No-Load Current (A)  | 2     |
| Full Load Torque    | 8.9            | 100                  | No-Load Power Factor | 0.07  |

**TYPICAL PERFORMANCE - NOT GUARANTEED VALUES**

| % OF RATED LOAD     | 25   | 50   | 75   | 100  | 125  | S.F. 1.25 |
|---------------------|------|------|------|------|------|-----------|
| Line Amperes (A)    | 2.1  | 2.3  | 2.7  | 3.1  | 3.6  | 3.6       |
| Efficiency (%)      | 77.8 | 86   | 88.4 | 89.1 | 89   | 89        |
| Speed (r/min)       | 1194 | 1190 | 1185 | 1179 | 1172 | 1172      |
| Power Factor (cosΦ) | 0.29 | 0.47 | 0.6  | 0.69 | 0.74 | 0.74      |
| Input Power (kW)    | 0.48 | 0.87 | 1.27 | 1.68 | 2.11 | 2.11      |

Questions? **Call 1.888.286.1820**




- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
  - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
  - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “\*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
  - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
  - 5. DIAGRAMS FOR REFERENCE ONLY



|                     |               |
|---------------------|---------------|
| DRAWING NUMBER:     | NEMA-3-9-YY-Y |
| CONNECTION:         | YY/Y          |
| NUMBER OF LEADS:    | 9             |
| THERMAL PROTECTION: | -             |

NEMA 3Ø YY/Y 9-Lead Dual Voltage

|                                  |          |
|----------------------------------|----------|
| ISSUED DATE                      | 11/03/25 |
| PREMIUM T-FRAME CAST IRON MOTORS |          |



NEMA Premium TEFC 184T

|                  |                    |                                  |          |
|------------------|--------------------|----------------------------------|----------|
| DRAWING NUMBER:  | GR3-CI-TF-184T-CFC | ISSUED DATE                      | 11/03/25 |
| DIMENSIONS:      | Inches             | PREMIUM T-FRAME CAST IRON MOTORS |          |
| MOUNTING:        | Rigid              |                                  |          |
| CASING MATERIAL: | Cast Iron          |                                  |          |