

NEMA

Model GRC1502F-TD
MFG PN: T445T 150U2B

Model GRC1502F-TD

Product Data Package



MODEL	HP	RPM	VOLTAGE	PHASE	Hz	FRAME	MOUNT	ENCLOSURE
GRC1502F-TD	150	3570	575	3	60	445TSD	Rigid/D-Flange	TEFC

Toronto

TOLL FREE 1.888.286.1820
PHONE 905.829.1001
EMAIL info@techtopcanada.com

Montreal

TOLL FREE 1.844.354.5111
PHONE 514.354.1002
EMAIL infoQC@techtopcanada.com

Moncton


PHONE 506.386.5794
EMAIL infoNB@techtopcanada.com

Winnipeg

PHONE 204.633.2779
EMAIL infoMB@techtopcanada.com

Vancouver

PHONE 604.525.1551
EMAIL infoBC@techtopcanada.com



Index

Motor General Data Sheet	P 2
Nameplate Information	P 3
Technical Performance Data	P 4
Motor General Wiring Diagram	P 5
Motor General Outline Drawing	P 6

NEMA

Model GRC1502F-TD
MFG PN: T445T 150U2B


ELECTRICAL DATA		
Rated Motor Output Power	150	HP
	-	kW
Rated Motor Speed	3570	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	575	V/60Hz
	-	V/50Hz
Rated Motor Current	127.18	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	3	Ø
Locked Rotor Current @ High Voltage	1057.6	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	1	@ 50Hz
KVA Code	H	60Hz
	-	50Hz
Nominal Efficiency	95	% @ 60Hz
Nominal Power Factor	0.93	cosΦ @ 60Hz
Leads (Qty, Size)	6	2
Connection	D	-
Coil Resistance	10	Ω
Start Capacitor	-	µF/V
Run Capacitor	-	µF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	81.7	°C @ 60Hz
	118.7	°C @ 50Hz

GENERAL DATA		
Frame Size	445TSD	
Enclosure	TEFC	
Mounting	Rigid/D-Flange	
Approximate Weight (lbs.)	1597 lbs.	
Casing Material / Fan Cover	Cast Iron	Cast Iron
Shaft Material	4140	
NEMA Design	A	
Degree of Protection (IP)	55	
Insulation Class / Temp Rise (60Hz)	F	B
Tropicalization	YES	
Duty	Cont. / S1	
Conduit Box Location	F1	
Feet Removable / Double Drilled	NO	YES
Paintwork	7024	
	Graphite Gray	
MECHANICAL DATA		
Bearing DE Side	6316 C3	
Bearing ODE Side	6316 C3	
Grease Type	Mobil Polyrex EM	
Compensation Ring (wavy washer)	NDE	
Moment of Inertia (lb-ft²)	25.93	
Sound Pressure @ 3 FT dBA	93.1	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	A, B, C & D	
Temperature Code	T3A	-

Questions? Call 1.888.286.1820

NEMA

Model GRC1502F-TD
MFG PN: T445T 150U2B



NAMEPLATE DATA	60Hz	50Hz
Horse Power	150	150
RPM	3570	-
Voltage	575	-
Full Load Amps	127.18	-
Service Factor	1.15	1
KVA Code	H	-
Full Load Amps (208V)	-	-
Nominal Efficiency	95	-
Nominal Power Factor	0.93	-
Design	A	
Frame	445TSD	
Enclosure Type	TEFC	
IP Rating	55	
Duty	Cont. / S1	
Insulation Class	F	
Ambient Rating	40	
Drive End Bearing	6316 C3	
Opposite Drive End Bearing	6316 C3	
Weight (lbs)	1597	

NAMEPLATE LAYOUT

TECHTOP		INDUSTRIAL THREE PHASE MOTOR INVERTER DUTY 15:1 CT 30:1 VT - 1.0 SF	
MODEL		TECHTOPCANADA.COM	
NEMA Premium		60Hz	50Hz
HP		MFG PN	
RPM		MFG DATE	
VOLT		SER #	
FLA		DESIGN	
SF		FRAME	
KVA CODE		ENCL	
NOM.EFF		IP	
BEARING SIZE		DUTY	
DE	ODE	INS CL	
GREASE: MOBIL POLYREX EM		AMB	
MADE IN CHINA CLASS 1, DIV 2, GROUPS A, B, C AND D		WEIGHT	
		lbs	
		Energy Verified	
		IEEE 45 MARINE DUTY	

VFD DUTY (S.F. 1.0)	RATIO	Hz*
Variable Torque	30:1	2 - 60
Constant Torque	15:1	4 - 60

*For max speed please contact Techtop Canada


HAZARDOUS LOCATIONS	CSA CERTIFIED
Class / Division	Class I, Div. 2
Groups	A, B, C & D

Questions? Call 1.888.286.1820

NEMA

Model GRC1502F-TD
MFG PN: T445T 150U2B

Torque Speed (T-n) Curve



PERFORMANCE LOAD VALUES, HIGH VOLTAGE, 60Hz

TORQUE VALUES	TORQUE (lb-ft)	TORQUE (% FULL LOAD)	PERFORMANCE VALUES	
Locked Rotor Torque	507.5	230	Start Configuration	DOL
Pull-Up Torque	229.5	104	Starting Current (A)	1057.6
Breakdown Torque	606.8	275	No-Load Current (A)	21.8
Full Load Torque	220.7	100	No-Load Power Factor	0.1

TYPICAL PERFORMANCE - NOT GUARANTEED VALUES

% OF RATED LOAD	25	50	75	100	125	S.F. 1.15
Line Amperes (A)	37.9	64.7	93.6	124.4	157.1	147
Efficiency (%)	91.7	94.5	95	94.7	94.2	94.2
Speed (r/min)	3593	3586	3578	3570	3561	3560
Power Factor (cosΦ)	0.8	0.9	0.93	0.94	0.93	0.93
Input Power (kW)	29.98	58.18	86.88	116.12	145.95	136.72

Questions? Call 1.888.286.1820



- NOTES:
- 1. CCW ROTATION FACING ODE FOR CONNECTIONS SHOWN
 - 2. TO REVERSE ROTATION, SWAP ANY TWO INPUT LINES
 - 3. WHEN MOTOR IS IN F1 POSITION, LEADS INDICATED WITH “*” EXIT THE CASING ABOVE THE CENTER LINE OF THE MOTOR, THE REMAINING LEADS EXIT BELOW THE CENTER LINE
 - 4. LEADS MUST BE NUMBERED AND COLORED AS SHOWN
 - 5. DIAGRAMS FOR REFERENCE ONLY



DRAWING NUMBER:	NEMA-3-6-D
CONNECTION:	D
NUMBER OF LEADS:	6
THERMAL PROTECTION:	-


NEMA 3Ø D 6-Lead Single Voltage

ISSUED DATE	06/06/25
PREMIUM T-FRAME CAST IRON MOTORS	

NEMA

Model **GRC1502F-TD**

MFG PN: T445T 150U2B



NEMA Premium TEFC 445TSD

DRAWING NUMBER:

GR3-CI-TF-444(5)TSD-CFC

DIMENSIONS:

Inches

MOUNTING:

Rigid/D-Flange

CASING MATERIAL:

Cast Iron

ISSUED DATE

06/06/25

PREMIUM T-FRAME CAST IRON MOTORS